

Antenna-Railway-5G-4L2WG

Railway Antenna with 4x4 MIMO 5G + MIMO WLAN + GNSS + 3m Cable

Omnidirectional multiband antenna for signal enhancement in 5G, 4G, 3G, 2G, WLAN networks and active GPS antenna.



Keyfeatures

WiFi / WLAN	MIMO 2.4 / 5 GHz
Cellular	MIMO 5G/ LTE / UMTS / GSM / GSM-R
GNSS	active
Railway	EN50155, EN45545

Specifications

Mobile / Cellular	Standard	<p>4 x LTE / UMTS / GSM / GSM-R / 5G</p> <p>LTE Bands: 1, 2, 3, 4, 5, 7, 8, 10, 12, 13, 14, 17, 18, 19, 20, 23, 25, 26, 27, 28, 29, 30, 65, 66, 67, 68, 69, 70, 85 - TDD Bands: 33, 34, 35, 36, 37, 38, 39, 40, 41, 44, 53 , 5G Bands: 1, 2, 3, 5, 7, 8, 20, 25, 65, 66, 70, 80, 81, 82, 83, 84, 86 - TDD Bands: 34, 38, 39, 40, 41, 78</p> <p>UMTS Bands: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 12, 13, 14, 19, 20, 25, 26 - TDD Bands: 33, 34, 35, 36, 37, 38, 39, 40</p> <p>GSM Bands: 710, 750, 810 T-GSM, 850, 900 P, 900 E, 900 R, 1800 DCS, 1900 PCS</p> <p>Bands 710, 750, 810 T-GSM, 850, 900 P, 900 E, 900 R, 1800 DCS, 1900 PCS</p> <p>Frequency 694 - 960, 1710 - 2690, 3100 - 3800</p>
	Specification	<p>Gain 7,2 dBi (LTE 700, GSM-R) / 7,9 dBi (GSM 1800, UMTS), 10,5 dBi (LTE 2600, 5G)</p> <p>VSWR ≤ 1,8 typ.</p> <p>Impedance 50 Ohm</p> <p>Radiation omnidirectional</p>
	Connectors	<p>4x N female</p> <p>Type N</p> <p>Gender Female</p>
WiFi / WLAN	Standards	<p>2 x Dual-band WLAN 2.4/5 GHz</p> <p>Frequency 2400 - 2500, 5180 - 5835</p>
	Specification	<p>Gain 7,6 dBi (WLAN 2.4) / 8,1 dBi (WLAN 5)</p> <p>VSWR ≤ 1,8 typ.</p> <p>Impedance 50 Ohm</p> <p>Radiation omnidirectional</p>
	Connectors	<p>2x N female</p> <p>Type N</p> <p>Gender Female</p>
GNSS	Standards	<p>1 x GPS / Galileo / GLONASS / BeiDou</p> <p>Type active</p> <p>Frequency 1560 - 1606</p>
	Specification	<p>Gain 5.0 dBi</p> <p>VSWR ≤ 1,8 typ.</p> <p>Impedance 50 Ohm</p> <p>Radiation omnidirectional</p>
	Amplifier	<p>Power 3.3 - 5 V</p> <p>Current 8 mA typ. (3.3 V) / 15 mA typ. (5 V)</p> <p>Gain 25 dB typ.</p>
	Connectors	<p>1x N female</p> <p>Type N</p> <p>Gender Female</p> <p>0,3 m cable N-m angle to amplifier with N-f</p>

Mechanical	Dimensions	Diameter 200 mm
	Weight	Height 60 mm
	Mounting	1700 g
	Color	Rooftop with screws no ground plane needed black
Environment	Operating Temperature	-60°C to +85°C
	Ingress Protection Level	IPX9k IP6X
Certifications	Compliance Standards	EN 50155, EN 50122, EN 50124, IEC 60068, IEC 61373, ISO 20653, ISO 9227, EN 45545-2 2014/30/EU; 2006/28/EC; 2002/95/EC
	Domain	EN 50122, EN 50124, IEC 60068, IEC 61373, ISO20653, ISO 9227, 2006/28/EC; 2002/95/EC Railway
Extension Cables	Cellular	4 x Ant-Cable-Railway-01-Nm-TNCm-3 / 3 m / N male / TNC male
	WLAN	2 x Ant-Cable-Railway-01-Nm-TNCm-3 / 3 m / N male / TNC male
	GNSS	1 x Ant-Cable-Railway-01-Nm-TNCm-3 / 3 m / N male / TNC male
Other	Order Code	Antenna-Railway-5G-4L2WG