





Test Report issued under the responsibility of:



TEST REPORT IEC 62368-1 Audio/video, information and communication technology equipment Part 1: Safety requirements	
Report reference No. : 17-EL-0056.S02 Date of issue : 2017-12-13 Total number of pages : 70 CB Testing Laboratory : Electrosuisse Address : Luppmenstrasse 1 8320 Fehraltorf SWITZERLAND  	
Applicant's name : NetModule AG Address : Meriedweg 11, 3172 Niederwangen SWITZERLAND	
Test specification : Standard : IEC 62368-1:2014 (Second Edition) Test procedure : Type testing for CE Non-standard test method : N/A	
Test Report Form No. : IEC62368_1B Test Report Form(s) Originator : UL(US) Master TRF : 2014-03	
Copyright © 2014 Worldwide System for Conformity Testing and Certification of Electrotechnical Equipment and Components (IECEE), Geneva, Switzerland. All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed. This report is not valid as a CB Test Report unless signed by an approved CB Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.	
General disclaimer: The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Issuing CB Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the NCB, responsible for this Test Report.	
Test Item description	Wireless Router
Trade Mark	NetModule
Manufacturer	NetModule AG Meriedweg 11, 3172 Niederwangen SWITZERLAND
Model/Type reference	NB800
Ratings	12 - 24 V~, 0.4 A, 5 W

<input checked="" type="checkbox"/>	CB Testing Laboratory:	Electrosuisse
Testing location/ address		Luppenstrasse 1, 8320 Fehraltorf SWITZERLAND
<input type="checkbox"/>	Associated CB Testing Laboratory:	
Testing location/ address		
Tested by (name + signature)		Robert Kaufmann Project Engineer
Approved by (name + signature)		Walter Fäh Project Engineer
<input type="checkbox"/>	Testing procedure: TMP/CTF Stage 1	
Testing location/ address		
Tested by (name + signature)		
Approved by (name + signature)		
<input type="checkbox"/>	Testing procedure: WMT/CTF Stage 2	
Testing location/ address		
Tested by (name + signature)		
Witnessed by (name + signature)		
Approved by (name + signature)		
<input type="checkbox"/>	Testing procedure: SMT/CTF Stage 3 or 4	
Testing location/ address		
Tested by (name + signature)		
Approved by (name + signature)		
Supervised by (name + signature)		

List of Attachments (including a total number of pages in each attachment):

- Appendix List of Test Equipment: 1 page
- ATTACHMENT TO TEST REPORT IEC 62368-1, EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES: 13 pages
- Attachment Photo Documentation: 5 pages

Summary of testing:

The equipment complies with this standard.

Conditions of acceptability:

It must be ensured by installation that the input current of each router cannot exceed 8 A. This could be accomplished a) with a limited power supply output current of max. 8 A or b) with a single series fuse (8 A delayed) at V+ input of the router.

Furthermore, power supply wires attached to V+ and V- inputs of the router must be able to withstand to a current up to 8 A without heating up significantly or damaging its isolation.

See also instructions in "User Manual: 4.8 Installation of the Power Supply".

Tests performed (name of test and test clause):**Complete test performed**

- 4.1.2.....:List of critical components
- 5.2.....: Classification of electrical energy sources
- 5.4.1.4.....: Temperature measurements
- 5.4.2/3.....: Minimum Clearances/Creepage distance
- 5.4.9.....:Electric strength tests
- 6.2.2.....:Electrical power sources (PS) measurements for classification
- 6.2.3.....:Determination of Potential Ignition Sources
- B.2.5.....: Input test
- B.3.....:Abnormal operating condition tests
- B.4.....:Fault condition tests
- T.2/3/4/5...:Steady force test
- T.6.....:Impact tests

This test report No. 17-EL-0056.S02 replaces the test report No. 17-EL-0056.S01, dated 2017-05-08.

History of changes

- Additional variants added, see Model Differences
- Tests with equipped COM_I/O module (isolated I/Os) added
- List of critical components adjusted
- National Differences updated to EN 62368-1:2014+A11:2017

Testing location:

**Electrosuisse Albislab
Albisriederstrasse 199, 8047 Zürich
SWITZERLAND**


Summary of compliance with National Differences:

List of countries addressed: CENELEC

☒ The product fulfils the requirements of EN 62368-1:2014+A11:2017

Copy of marking plate:

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.



Note: Depending on the implemented radio modules, additional letters and numbers may be added to "NB800".

TEST ITEM PARTICULARS:	
Classification of use by	<input checked="" type="checkbox"/> Ordinary person <input type="checkbox"/> Instructed person <input type="checkbox"/> Skilled person <input type="checkbox"/> Children likely to be present
Supply Connection	<input type="checkbox"/> AC Mains <input checked="" type="checkbox"/> DC Mains <input type="checkbox"/> External Circuit - not Mains connected - <input checked="" type="checkbox"/> ES1 <input type="checkbox"/> ES2 <input type="checkbox"/> ES3
Supply % Tolerance	<input type="checkbox"/> +10 %/-10 % <input type="checkbox"/> +20 %/-15 % <input checked="" type="checkbox"/> +20 %/ -20 % <input type="checkbox"/> None
Supply Connection – Type	<input type="checkbox"/> pluggable equipment type A - <input type="checkbox"/> non-detachable supply cord <input type="checkbox"/> appliance coupler <input type="checkbox"/> direct plug-in <input type="checkbox"/> mating connector <input type="checkbox"/> pluggable equipment type B - <input type="checkbox"/> non-detachable supply cord <input type="checkbox"/> appliance coupler <input type="checkbox"/> permanent connection <input checked="" type="checkbox"/> mating connector <input type="checkbox"/> other: _____
Considered current rating of protective device as part of building or equipment installation.....	N/A Installation location: <input type="checkbox"/> building; <input type="checkbox"/> equipment
Equipment mobility	<input type="checkbox"/> movable <input type="checkbox"/> hand-held <input type="checkbox"/> transportable <input type="checkbox"/> stationary <input checked="" type="checkbox"/> for building-in <input type="checkbox"/> direct plug-in <input type="checkbox"/> rack-mounting <input checked="" type="checkbox"/> wall-mounted
Over voltage category (OVC)	<input checked="" type="checkbox"/> OVC I <input type="checkbox"/> OVC II <input type="checkbox"/> OVC III <input type="checkbox"/> OVC IV <input type="checkbox"/> other: _____
Class of equipment	<input type="checkbox"/> Class I <input type="checkbox"/> Class II <input type="checkbox"/> Class III
Access location	<input type="checkbox"/> restricted access location <input checked="" type="checkbox"/> N/A
Pollution degree (PD)	<input type="checkbox"/> PD 1 <input checked="" type="checkbox"/> PD 2 <input type="checkbox"/> PD 3
Manufacturer's specified maximum operating ambient	70 °C
IP protection class	<input type="checkbox"/> IPX0 <input checked="" type="checkbox"/> IP40, with SIM cover
Power Systems	<input type="checkbox"/> TN <input type="checkbox"/> TT <input type="checkbox"/> IT - ____ V _{L-L}
Altitude during operation (m)	<input type="checkbox"/> 2000 m or less <input checked="" type="checkbox"/> 4000 m
Altitude of test laboratory (m)	<input checked="" type="checkbox"/> 2000 m or less <input type="checkbox"/> ____ m
Mass of equipment (kg)	<input checked="" type="checkbox"/> 0.2 kg
POSSIBLE TEST CASE VERDICTS:	
- test case does not apply to the test object.....	N/A
- test object does meet the requirement.....	P (Pass)
- test object does not meet the requirement.....	F (Fail)
TESTING:	
Date of receipt of test item	2017-03-16
Date (s) of performance of tests	2017-03-16 to 2017-12-13

GENERAL REMARKS:

"(See Enclosure #)" refers to additional information appended to the report.

"(See appended table)" refers to a table appended to the report.

Throughout this report a ☐ comma / ☒ point is used as the decimal separator.

Manufacturer's Declaration per sub-clause 4.2.5 of IEC60060-2:

The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided.....

☐ **Yes**
☒ **Not applicable**


When differences exist; they shall be identified in the General product information section.

Name and address of factory (ies)

NetModule AG
 Meriedweg 11
 3172 Niederwangen
 SWITZERLAND

GENERAL PRODUCT INFORMATION:**Product Description –**

The EUT is a versatile router for a multiplicity of communication interfaces (wired and radio interfaces).



Overall size of equipment (W x D x H): 99 mm x 111 mm x 32 mm

Model Differences –

Note: Depending on the implemented radio modules, additional letters and numbers may be added to “NB800”.

Tested Equipment	Covered Variants	Explanation ¹⁾																																																									
NB800-LWWt, NB800-LWWtSu NB800-LWWtScSu	NB800-H ₁ ...H _n - S ₁ ...S _n -S-O ₁ ...O _n	<p>All covered NB800 variants contain the same mainboard (PCB), have the same case and the same form factor. They can provide 3G or 4G mobile network access. Optionally WLAN, Bluetooth and USB functionality can be included. Optionally, different interfaces can be included as extension boards called 'shields' (order code Sc for COMIO, 2C for 2xCAN).</p> <p>There can be up to 4 antenna connectors.</p> <p>The wireless communication modules applied have been CE and FCC certified in an independent way of the tested equipment.</p> <p>'H₁...H_n' is a sequence of the following letters that identify the communication modules included:</p> <table><tr><td>B</td><td>basic device</td><td></td></tr><tr><td>R</td><td>none</td><td></td></tr><tr><td>U</td><td>3G+ = 2G + UMTS/HSPA/HSPA+</td><td>UMTS</td></tr><tr><td>Ub</td><td>3G North America</td><td>UMTS-NA</td></tr><tr><td>L</td><td>4G = 3G+ + LTE</td><td>LTE</td></tr><tr><td>Lb</td><td>4G North America</td><td>LTE-NA</td></tr><tr><td>W</td><td>WLAN a/b/g/n 2.4/5 GHz</td><td>WLAN 11a/b/g/n</td></tr><tr><td>Wb</td><td>WLAN b/g 2.4 GHz</td><td>WLAN 11b/g</td></tr><tr><td>Wt</td><td>Bluetooth + BLE</td><td>BT</td></tr><tr><td>Wz</td><td>Zigbee</td><td></td></tr><tr><td>Su</td><td>USB Host Port</td><td>USB</td></tr><tr><td>Ra</td><td>256MB RAM (Standard for UMTS)</td><td></td></tr><tr><td>Rb</td><td>512MB RAM (Standard for LTE)</td><td></td></tr><tr><td>Sc</td><td>RS232/485 + Digital IO (shield)</td><td>COMIO</td></tr><tr><td>2C</td><td>Dual CAN (shield)</td><td>2xCAN</td></tr></table> <p>'S₁...S_n' indicate software options activated:</p> <table><tr><td>V</td><td>VoIP Gateway</td></tr><tr><td>Y</td><td>Plain Linux</td></tr><tr><td>Vi</td><td>Virtualisation, LXC</td></tr></table> <p>'O' indicates OEM options, typ. customer brand labeling e.g.:</p> <table><tr><td>TAG</td><td>Tagfinder</td></tr><tr><td>OEMa</td><td>Customer A</td></tr><tr><td>OEMb</td><td>Customer B</td></tr></table>	B	basic device		R	none		U	3G+ = 2G + UMTS/HSPA/HSPA+	UMTS	Ub	3G North America	UMTS-NA	L	4G = 3G+ + LTE	LTE	Lb	4G North America	LTE-NA	W	WLAN a/b/g/n 2.4/5 GHz	WLAN 11a/b/g/n	Wb	WLAN b/g 2.4 GHz	WLAN 11b/g	Wt	Bluetooth + BLE	BT	Wz	Zigbee		Su	USB Host Port	USB	Ra	256MB RAM (Standard for UMTS)		Rb	512MB RAM (Standard for LTE)		Sc	RS232/485 + Digital IO (shield)	COMIO	2C	Dual CAN (shield)	2xCAN	V	VoIP Gateway	Y	Plain Linux	Vi	Virtualisation, LXC	TAG	Tagfinder	OEMa	Customer A	OEMb	Customer B
B	basic device																																																										
R	none																																																										
U	3G+ = 2G + UMTS/HSPA/HSPA+	UMTS																																																									
Ub	3G North America	UMTS-NA																																																									
L	4G = 3G+ + LTE	LTE																																																									
Lb	4G North America	LTE-NA																																																									
W	WLAN a/b/g/n 2.4/5 GHz	WLAN 11a/b/g/n																																																									
Wb	WLAN b/g 2.4 GHz	WLAN 11b/g																																																									
Wt	Bluetooth + BLE	BT																																																									
Wz	Zigbee																																																										
Su	USB Host Port	USB																																																									
Ra	256MB RAM (Standard for UMTS)																																																										
Rb	512MB RAM (Standard for LTE)																																																										
Sc	RS232/485 + Digital IO (shield)	COMIO																																																									
2C	Dual CAN (shield)	2xCAN																																																									
V	VoIP Gateway																																																										
Y	Plain Linux																																																										
Vi	Virtualisation, LXC																																																										
TAG	Tagfinder																																																										
OEMa	Customer A																																																										
OEMb	Customer B																																																										

Tested Equipment	Covered Variants	Explanation ¹⁾																																																								
NB800-LWWt, NB800-LWWtSu NB800-LWWtScSu	NB800-H ₁ ...H _n - S ₁ ...S _n -S-O ₁ ...O _n	<p>The following NB800 variants are currently available or <i>planned</i>:</p> <p><u>UMTS Modem with Options:</u></p> <table><tr><td>NB800-U</td><td>UMTS</td></tr><tr><td>NB800-USu</td><td>+ USB</td></tr><tr><td>NB800-USc</td><td>+ COMIO</td></tr><tr><td>NB800-U2C</td><td>+ 2xCAN</td></tr><tr><td>NB800-UScSu</td><td>+ COMIO + USB</td></tr><tr><td>NB800-USu2C</td><td>+ USB + 2xCAN</td></tr></table> <p>NB800-UWWt UMTS + WLAN + BT</p> <table><tr><td>NB800-UWWtSu</td><td>+ USB</td></tr><tr><td>NB800-UWWtSc</td><td>+ COMIO</td></tr><tr><td>NB800-UWWt2C</td><td>+ 2xCAN</td></tr><tr><td>NB800-UWWtScSu</td><td>+ COMIO + USB</td></tr><tr><td>NB800-UWWtSu2C</td><td>+ USB + 2xCAN</td></tr></table> <p><i>NB800-Ub...</i> <i>UMTS modem for North America, and any of above options (replace U with Ub)</i></p> <p><u>LTE Modem with Options:</u></p> <table><tr><td>NB800-L</td><td>LTE</td></tr><tr><td>NB800-LSu</td><td>+ USB</td></tr><tr><td>NB800-LSc</td><td>+ COMIO</td></tr><tr><td>NB800-L2C</td><td>+ 2xCAN</td></tr><tr><td>NB800-LScSu</td><td>+ COMIO + USB</td></tr><tr><td>NB800-LSu2C</td><td>+ USB + 2xCAN</td></tr></table> <p>NB800-LWWt LTE + WLAN + BT</p> <table><tr><td>NB800-LWWtSu</td><td>+ USB</td></tr><tr><td>NB800-LWWtSc</td><td>+ COMIO</td></tr><tr><td>NB800-LWWt2C</td><td>+ 2xCAN</td></tr><tr><td>NB800-LWWtScSu</td><td>+ COMIO + USB</td></tr><tr><td>NB800-LWWtSu2C</td><td>+ USB + 2xCAN</td></tr></table> <p><i>NB800-Lb...</i> <i>LTE modem for North America, and any of above options (replace L with Lb)</i></p> <p><u>Base-Devices (no wireless interfaces):</u></p> <table><tr><td>NB800-B</td><td>no modem, no WLAN, but Ethernet</td></tr><tr><td>NB800-BSu</td><td>+ USB</td></tr><tr><td>NB800-BSc</td><td>+ COMIO</td></tr><tr><td>NB800-B2C</td><td>+ 2xCAN</td></tr><tr><td>NB800-BScSu</td><td>+ COMIO + USB</td></tr><tr><td>NB800-BSu2C</td><td>+ USB + 2xCAN</td></tr></table> <p><i>NB800-R...</i> <i>and any of above options (replace B with R in above options)</i></p>	NB800-U	UMTS	NB800-USu	+ USB	NB800-USc	+ COMIO	NB800-U2C	+ 2xCAN	NB800-UScSu	+ COMIO + USB	NB800-USu2C	+ USB + 2xCAN	NB800-UWWtSu	+ USB	NB800-UWWtSc	+ COMIO	NB800-UWWt2C	+ 2xCAN	NB800-UWWtScSu	+ COMIO + USB	NB800-UWWtSu2C	+ USB + 2xCAN	NB800-L	LTE	NB800-LSu	+ USB	NB800-LSc	+ COMIO	NB800-L2C	+ 2xCAN	NB800-LScSu	+ COMIO + USB	NB800-LSu2C	+ USB + 2xCAN	NB800-LWWtSu	+ USB	NB800-LWWtSc	+ COMIO	NB800-LWWt2C	+ 2xCAN	NB800-LWWtScSu	+ COMIO + USB	NB800-LWWtSu2C	+ USB + 2xCAN	NB800-B	no modem, no WLAN, but Ethernet	NB800-BSu	+ USB	NB800-BSc	+ COMIO	NB800-B2C	+ 2xCAN	NB800-BScSu	+ COMIO + USB	NB800-BSu2C	+ USB + 2xCAN
NB800-U	UMTS																																																									
NB800-USu	+ USB																																																									
NB800-USc	+ COMIO																																																									
NB800-U2C	+ 2xCAN																																																									
NB800-UScSu	+ COMIO + USB																																																									
NB800-USu2C	+ USB + 2xCAN																																																									
NB800-UWWtSu	+ USB																																																									
NB800-UWWtSc	+ COMIO																																																									
NB800-UWWt2C	+ 2xCAN																																																									
NB800-UWWtScSu	+ COMIO + USB																																																									
NB800-UWWtSu2C	+ USB + 2xCAN																																																									
NB800-L	LTE																																																									
NB800-LSu	+ USB																																																									
NB800-LSc	+ COMIO																																																									
NB800-L2C	+ 2xCAN																																																									
NB800-LScSu	+ COMIO + USB																																																									
NB800-LSu2C	+ USB + 2xCAN																																																									
NB800-LWWtSu	+ USB																																																									
NB800-LWWtSc	+ COMIO																																																									
NB800-LWWt2C	+ 2xCAN																																																									
NB800-LWWtScSu	+ COMIO + USB																																																									
NB800-LWWtSu2C	+ USB + 2xCAN																																																									
NB800-B	no modem, no WLAN, but Ethernet																																																									
NB800-BSu	+ USB																																																									
NB800-BSc	+ COMIO																																																									
NB800-B2C	+ 2xCAN																																																									
NB800-BScSu	+ COMIO + USB																																																									
NB800-BSu2C	+ USB + 2xCAN																																																									

Tested Equipment	Covered Variants	Explanation ¹⁾												
NB800-LWWt, NB800-LWWtSu NB800-LWWtScSu	NB800-H ₁ ...H _n - S ₁ ...S _n -S-O ₁ ...O _n	<p>The following NB800 variants are currently available or <i>planned</i>:</p> <p><u>No Cellular Modem:</u></p> <table><tr><td>NB800-WWt</td><td>WLAN + BT</td></tr><tr><td>NB800-WWtSu</td><td>+ USB</td></tr><tr><td>NB800-WWtSc</td><td>+ COMIO</td></tr><tr><td>NB800-WWt2C</td><td>+ 2xCAN</td></tr><tr><td>NB800-WWtScSu</td><td>+ COMIO + USB</td></tr><tr><td>NB800-WWtSu2C</td><td>+ USB + 2xCAN</td></tr></table> <p><u>SW Options:</u> Add suffix for any SW option, e.g. -Y for plain Linux, -Vi for LX Container Examples: NB800-LWWtSu-Y NB800-LWWtSu-Vi NB800-LWWtScSu-Y NB800-LWWtSu2C-Vi</p> <p><u>OEM Options:</u> Add suffix -TAG, -OEM1, -OEM2 for OEM branding options (logo print), e.g. NB800-LWWt-TAG</p>	NB800-WWt	WLAN + BT	NB800-WWtSu	+ USB	NB800-WWtSc	+ COMIO	NB800-WWt2C	+ 2xCAN	NB800-WWtScSu	+ COMIO + USB	NB800-WWtSu2C	+ USB + 2xCAN
NB800-WWt	WLAN + BT													
NB800-WWtSu	+ USB													
NB800-WWtSc	+ COMIO													
NB800-WWt2C	+ 2xCAN													
NB800-WWtScSu	+ COMIO + USB													
NB800-WWtSu2C	+ USB + 2xCAN													
1) according to information of the customer and not verified by Eurofins Electrosuisse														
Additional application considerations – (Considerations used to test a component or sub-assembly) – None														

ENERGY SOURCE IDENTIFICATION AND CLASSIFICATION TABLE:	
(Note 1: Identify the following six (6) energy source forms based on the origin of the energy.) (Note 2: The identified classification e.g., ES2, TS1, should be with respect to its ability to cause pain or injury on the body or its ability to ignite a combustible material. Any energy source can be declared Class 3 as a worse case classification e.g. PS3, ES3.)	
Electrically-caused injury (Clause 5): (Note: Identify type of source, list sub-assembly or circuit designation and corresponding energy source classification) Example: +5 V dc input ES1	
Source of electrical energy	Corresponding classification (ES)
All circuits	ES1
---	---
Electrically-caused fire (Clause 6): (Note: List sub-assembly or circuit designation and corresponding energy source classification) Example: Battery pack (maximum 85 watts): PS2	
Source of power or PIS	Corresponding classification (PS)
Power input circuits	PS3
+5V0, +5V0_USB circuits	PS1
Injury caused by hazardous substances (Clause 7) (Note: Specify hazardous chemicals, whether produces ozone or other chemical construction not addressed as part of the component evaluation.) Example: Liquid in filled component Glycol	
Source of hazardous substances	Corresponding chemical
N/A	N/A
---	---
Mechanically-caused injury (Clause 8) (Note: List moving part(s), fan, special installations, etc. & corresponding MS classification based on Table 35.) Example: Wall mount unit MS2	
Source of kinetic/mechanical energy	Corresponding classification (MS)
Sharp edges & corners	MS1
Fixed device, ≤ 2 m	MS1
Thermal burn injury (Clause 9) (Note: Identify the surface or support, and corresponding energy source classification based on type of part, location, operating temperature and contact time in Table 38.) Example: Hand-held scanner – thermoplastic enclosure TS1	
Source of thermal energy	Corresponding classification (TS)
Accessible surfaces	TS1
---	---
Radiation (Clause 10) (Note: List the types of radiation present in the product and the corresponding energy source classification.) Example: DVD – Class 1 Laser Product RS1	
Type of radiation	Corresponding classification (RS)
LED indicators	RS1
---	---

ENERGY SOURCE DIAGRAM

Indicate which energy sources are included in the energy source diagram. Insert diagram below

☐ **ES** ☐ **PS** ☐ **MS** ☐ **TS** ☐ **RS**

OVERVIEW OF EMPLOYED SAFEGUARDS				
Clause	Possible Hazard			
5.1	Electrically-caused injury			
Body Part (e.g. Ordinary)	Energy Source (ES3: Primary Filter circuit)	Safeguards		
		Basic	Supplementary	Reinforced (Enclosure)
Ordinary	ES1: All circuits	N/A	N/A	N/A
---	---	---	---	---
6.1	Electrically-caused fire			
Material part (e.g. mouse enclosure)	Energy Source (PS2: 100 Watt circuit)	Safeguards		
		Basic	Supplementary	Reinforced
All combustible materials within equipment fire enclosure	PS3: Power input circuits	No excessive temp.	Suitable material	N/A
All materials within equipment fire enclosure	PS1 : +5V0, +5V0_USB circuits	N/A	N/A	N/A
7.1	Injury caused by hazardous substances			
Body Part (e.g., skilled)	Energy Source (hazardous material)	Safeguards		
		Basic	Supplementary	Reinforced
---	---	---	---	---
---	---	---	---	---
8.1	Mechanically-caused injury			
Body Part (e.g. Ordinary)	Energy Source (MS3:High Pressure Lamp)	Safeguards		
		Basic	Supplementary	Reinforced (Enclosure)
Ordinary	MS1: Sharp edges & corners	N/A	N/A	N/A
Ordinary	MS1: Fixed device, ≤ 2 m	N/A	N/A	N/A
9.1	Thermal Burn			
Body Part (e.g., Ordinary)	Energy Source (TS2)	Safeguards		
		Basic	Supplementary	Reinforced
Ordinary	TS1: Accessible surfaces	N/A	N/A	N/A
---	---	---	---	---
10.1	Radiation			
Body Part (e.g., Ordinary)	Energy Source (Output from audio port)	Safeguards		
		Basic	Supplementary	Reinforced
Ordinary	RS1: LED indicators	N/A	N/A	N/A
---	---	---	---	---
Supplementary Information: (1) See attached energy source diagram for additional details. (2) "N" – Normal Condition; "A" – Abnormal Condition; "S" Single Fault				

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
4	GENERAL REQUIREMENTS		P
4.1.1	Acceptance of materials, components and subassemblies		P
4.1.2	Use of components		P
4.1.3	Equipment design and construction		P
4.1.15	Markings and instructions	(See Annex F)	P
4.4.4	Safeguard robustness		P
4.4.4.2	Steady force tests	(See Annex T.4, T.5)	P
4.4.4.3	Drop tests.....	Fixed device (See Annex T.7)	N/A
4.4.4.4	Impact tests.....	(See Annex T.6)	P
4.4.4.5	Internal accessible safeguard enclosure and barrier tests	No such parts (See Annex T.3)	N/A
4.4.4.6	Glass Impact tests	(See Annex T.9, Annex U)	N/A
4.4.4.74	Thermoplastic material tests.....	(See Annex T.8)	N/A
4.4.4.8	Air comprising a safeguard	(See Annex T)	P
4.4.4.9	Accessibility and safeguard effectiveness		P
4.5	Explosion		N/A
4.6	Fixing of conductors		P
4.6.1	Fix conductors not to defeat a safeguard		P
4.6.2	10 N force test applied to	Internal components	P
4.7	Equipment for direct insertion into mains socket - outlets	No mains	N/A
4.7.2	Mains plug part complies with the relevant standard..		N/A
4.7.3	Torque (Nm).....	---	N/A
4.8	Products containing coin/button cell batteries		N/A
4.8.2	Instructional safeguard		N/A
4.8.3	Battery Compartment Construction	No battery	N/A
	Means to reduce the possibility of children removing the battery	---	—
4.8.4	Battery Compartment Mechanical Tests	(See Table 4.8.4)	N/A
4.8.5	Battery Accessibility		N/A
4.9	Likelihood of fire or shock due to entry of conductive object	No openings, without SIM cover only small SIM card slots, can't be entry (See Annex P)	P

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
5	ELECTRICALLY-CAUSED INJURY		P
5.2.1	Electrical energy source classifications	ES1: All circuits (See appended table 5.2)	P
5.2.2	ES1, ES2 and ES3 limits		P
5.2.2.2	Steady-state voltage and current	(See appended table 5.2)	P
5.2.2.3	Capacitance limits.....	(See appended table 5.2)	N/A
5.2.2.4	Single pulse limits	(See appended table 5.2)	N/A
5.2.2.5	Limits for repetitive pulses	(See appended table 5.2)	N/A
5.2.2.6	Ringing signals	(See Annex H)	N/A
5.2.2.7	Audio signals	(See Clause E.1)	N/A
5.3	Protection against electrical energy sources		N/A
5.3.1	General Requirements for accessible parts to ordinary, instructed and skilled persons		N/A
5.3.2.1	Accessibility to electrical energy sources and safeguards		N/A
5.3.2.2	Contact requirements		N/A
	a) Test with test probe from Annex V.....	ES1 voltages less than 60 VDC	N/A
	b) Electric strength test potential (V).....	---	N/A
	c) Air gap (mm)	---	N/A
5.3.2.4	Terminals for connecting stripped wire		N/A
5.4	Insulation materials and requirements		P
5.4.1.2	Properties of insulating material		P
5.4.1.3	Humidity conditioning.....	No hygroscopic material (See sub-clause 5.4.8)	N/A
5.4.1.4	Maximum operating temperature for insulating materials	(See appended table 5.4.1.4)	P
5.4.1.5	Pollution degree	2	—
5.4.1.5.2	Test for pollution degree 1 environment and for an insulating compound		N/A
5.4.1.5.3	Thermal cycling		N/A
5.4.1.6	Insulation in transformers with varying dimensions		N/A
5.4.1.7	Insulation in circuits generating starting pulses		N/A
5.4.1.8	Determination of working voltage		P
5.4.1.9	Insulating surfaces		N/A
5.4.1.10	Thermoplastic parts on which conductive metallic parts are directly mounted		N/A
5.4.1.10.2	Vicat softening temperature	(See appended table 5.4.1.10.2)	N/A
5.4.1.10.3	Ball pressure	(See appended table 5.4.1.10.3)	N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
5.4.2	Clearances		P
5.4.2.2	Determining clearance using peak working voltage	(See appended table 5.4.2.2)	P
5.4.2.3	Determining clearance using required withstand voltage	(See appended table 5.4.2.3)	P
	a) a.c. mains transient voltage..... :	---	—
	b) d.c. mains transient voltage	500 V _{peak}	—
	c) external circuit transient voltage..... :	1'500 V _{peak} (Ethernet)	—
	d) transient voltage determined by measurement... :	---	—
5.4.2.4	Determining the adequacy of a clearance using an electric strength test	(See appended table 5.4.2.4)	N/A
5.4.2.5	Multiplication factors for clearances and test voltages	up to 4000 m	P
5.4.3	Creepage distances..... :	(See appended table 5.4.3)	P
5.4.3.1	General		P
5.4.3.3	Material Group	IIIb	—
5.4.4	Solid insulation		P
5.4.4.2	Minimum distance through insulation	(See appended table 5.4.4.2)	N/A
5.4.4.3	Insulation compound forming solid insulation		N/A
5.4.4.4	Solid insulation in semiconductor devices		N/A
5.4.4.5	Cemented joints		N/A
5.4.4.6	Thin sheet material		N/A
5.4.4.6.1	General requirements		N/A
5.4.4.6.2	Separable thin sheet material		N/A
	Number of layers (pcs)	---	N/A
5.4.4.6.3	Non-separable thin sheet material		N/A
5.4.4.6.4	Standard test procedure for non-separable thin sheet material	(See appended Table 5.4.9)	N/A
5.4.4.6.5	Mandrel test		N/A
5.4.4.7	Solid insulation in wound components		N/A
5.4.4.9	Solid insulation at frequencies >30 kHz..... :	(See appended Table 5.4.4.9)	N/A
5.4.5	Antenna terminal insulation		N/A
5.4.5.1	General		N/A
5.4.5.2	Voltage surge test		N/A
	Insulation resistance (MΩ)..... :		—
5.4.6	Insulation of internal wire as part of supplementary safeguard	(See appended table 5.4.4.2)	N/A
5.4.7	Tests for semiconductor components and for cemented joints		N/A
5.4.8	Humidity conditioning		N/A
	Relative humidity (%)..... :	---	—

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Temperature (°C)	---	---
	Duration (h)	---	---
5.4.9	Electric strength test	(See appended table 5.4.9)	P
5.4.9.1	Test procedure for a solid insulation type test		P
5.4.9.2	Test procedure for routine tests		N/A
5.4.10	Protection against transient voltages between external circuit		P
5.4.10.1	Parts and circuits separated from external circuits	(See appended table 5.4.9)	P
5.4.10.2	Test methods		P
5.4.10.2.1	General		P
5.4.10.2.2	Impulse test.....	(See appended table 5.4.9)	N/A
5.4.10.2.3	Steady-state test.....	(See appended table 5.4.9)	P
5.4.11	Insulation between external circuits and earthed circuitry.....	(See appended table 5.4.9)	N/A
5.4.11.1	Exceptions to separation between external circuits and earth		N/A
5.4.11.2	Requirements		N/A
	Rated operating voltage U_{op} (V).....	---	---
	Nominal voltage U_{peak} (V).....	---	---
	Max increase due to variation U_{sp}	---	---
	Max increase due to ageing ΔU_{sa}	---	---
	$U_{op} = U_{peak} + \Delta U_{sp} + \Delta U_{sa}$	---	---
5.5	Components as safeguards		P
5.5.1	General		P
5.5.2	Capacitors and RC units		N/A
5.5.2.1	General requirement		N/A
5.5.2.2	Safeguards against capacitor discharge after disconnection of a connector	(See appended table 5.5.2.2)	N/A
5.5.3	Transformers	(See Annex G.5.3)	N/A
5.5.4	Optocouplers	(See sub-clause 5.4 or Annex G.12)	P
5.5.5	Relays	(See Annex G.2)	P
5.5.6	Resistors	(See Annex G.10)	N/A
5.5.7	SPD's	(See Annex G.8)	N/A
5.5.7.1	Use of an SPD connected to reliable earthing		N/A
5.5.7.2	Use of an SPD between mains and protective earth		N/A
5.5.8	Insulation between the mains and external circuit consisting of a coaxial cable	(See Annex G.10.3)	N/A
5.6	Protective conductor		N/A
5.6.2	Requirement for protective conductors		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
5.6.2.1	General requirements		N/A
5.6.2.2	Colour of insulation		N/A
5.6.3	Requirement for protective earthing conductors		N/A
	Protective earthing conductor size (mm ²) :	---	—
5.6.4	Requirement for protective bonding conductors		N/A
5.6.4.1	Protective bonding conductors		N/A
	Protective bonding conductor size (mm ²). :	---	—
	Protective current rating (A) :	---	—
5.6.4.3	Current limiting and overcurrent protective devices		N/A
5.6.5	Terminals for protective conductors		N/A
5.6.5.1	Requirement		N/A
	Conductor size (mm ²), nominal thread diameter (mm)..... :	---	N/A
5.6.5.2	Corrosion		N/A
5.6.6	Resistance of the protective system		N/A
5.6.6.1	Requirements		N/A
5.6.6.2	Test Method Resistance (Ω)..... :	(See appended table 5.6.6.2)	N/A
5.6.7	Reliable earthing		N/A
5.7	Prospective touch voltage, touch current and protective conductor current		N/A
5.7.2	Measuring devices and networks		N/A
5.7.2.1	Measurement of touch current..... :	(See appended table 5.7.4)	N/A
5.7.2.2	Measurement of prospective touch voltage		N/A
5.7.3	Equipment set-up, supply connections and earth connections		N/A
	System of interconnected equipment (separate connections/single connection)..... :	---	—
	Multiple connections to mains (one connection at a time/simultaneous connections) :	---	—
5.7.4	Earthed conductive accessible parts :	(See appended Table 5.7.4)	N/A
5.7.5	Protective conductor current		N/A
	Supply Voltage (V)..... :	---	—
	Measured current (mA)..... :	---	—
	Instructional Safeguard..... :	(See F.4 and F.5)	N/A
5.7.6	Prospective touch voltage and touch current due to external circuits		N/A
5.7.6.1	Touch current from coaxial cables		N/A
5.7.6.2	Prospective touch voltage and touch current from external circuits		N/A
5.7.7	Summation of touch currents from external circuits		N/A
	a) Equipment with earthed external circuits Measured current (mA)..... :	---	N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	b) Equipment whose external circuits are not referenced to earth. Measured current (mA) :	---	N/A
6	ELECTRICALLY- CAUSED FIRE		P
6.2	Classification of power sources (PS) and potential ignition sources (PIS)		P
6.2.2	Power source circuit classifications		P
6.2.2.1	General		P
6.2.2.2	Power measurement for worst-case load fault... :	(See appended table 6.2.2)	P
6.2.2.3	Power measurement for worst-case power source fault..... :	(See appended table 6.2.2)	P
6.2.2.4	PS1 :	+5V0, +5V0_USB circuits (See appended table 6.2.2)	P
6.2.2.5	PS2 :	No such circuits (See appended table 6.2.2)	N/A
6.2.2.6	PS3 :	Power input circuits (See appended table 6.2.2)	P
6.2.3	Classification of potential ignition sources		P
6.2.3.1	Arcing PIS :	No arcing PIS (See appended table 6.2.3.1)	N/A
6.2.3.2	Resistive PIS :	All PIS within fire enclosure (See appended table 6.2.3.2)	P
6.3	Safeguards against fire under normal operating and abnormal operating conditions		P
6.3.1 (a)	No ignition and attainable temperature value less than 90 % defined by ISO 871 or less than 300 °C for unknown materials..... :	(See appended table 5.4.1.5, 6.3.2, 9.0, B.2.6)	P
6.3.1 (b)	Combustible materials outside fire enclosure		N/A
6.4	Safeguards against fire under single fault conditions		P
6.4.1	Safeguard Method		P
6.4.2	Reduction of the likelihood of ignition under single fault conditions in PS1 circuits		P
6.4.3	Reduction of the likelihood of ignition under single fault conditions in PS2 and PS3 circuits		P
6.4.3.1	General		P
6.4.3.2	Supplementary Safeguards		P
	Special conditions if conductors on printed boards are opened or peeled		N/A
6.4.3.3	Single Fault Conditions..... :	(See appended table 6.4.3)	P
	Special conditions for temperature limited by fuse		N/A
6.4.4	Control of fire spread in PS1 circuits		P
6.4.5	Control of fire spread in PS2 circuits		N/A
6.4.5.2	Supplementary safeguards :	(See appended tables 4.1.2 and Annex G)	N/A
6.4.6	Control of fire spread in PS3 circuit		P

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
6.4.7	Separation of combustible materials from a PIS		N/A
6.4.7.1	General	(See tables 6.2.3.1 and 6.2.3.2)	N/A
6.4.7.2	Separation by distance		N/A
6.4.7.3	Separation by a fire barrier		N/A
6.4.8	Fire enclosures and fire barriers		P
6.4.8.1	Fire enclosure and fire barrier material properties		P
6.4.8.2.1	Requirements for a fire barrier		N/A
6.4.8.2.2	Requirements for a fire enclosure	Metal	P
6.4.8.3	Constructional requirements for a fire enclosure and a fire barrier		P
6.4.8.3.1	Fire enclosure and fire barrier openings	No openings, without SIM cover only small SIM card slots	P
6.4.8.3.2	Fire barrier dimensions		N/A
6.4.8.3.3	Top Openings in Fire Enclosure: dimensions (mm)	No openings	P
	Needle Flame test		N/A
6.4.8.3.4	Bottom Openings in Fire Enclosure, condition met a), b) and/or c) dimensions (mm)	No openings	P
	Flammability tests for the bottom of a fire enclosure	---	N/A
6.4.8.3.5	Integrity of the fire enclosure, condition met: a), b) or c).....	No door or cover that can be opened	N/A
6.4.8.4	Separation of PIS from fire enclosure and fire barrier distance (mm) or flammability rating.....	---	N/A
6.5	Internal and external wiring		N/A
6.5.1	Requirements	No int. wiring in PS3 circuits, ext. wiring not part of the EUT	N/A
6.5.2	Cross-sectional area (mm ²)	---	—
6.5.3	Requirements for interconnection to building wiring :	(See Annex Q.)	N/A
6.6	Safeguards against fire due to connection to additional equipment		N/A
	External port limited to PS2 or complies with Clause Q.1		N/A
7	INJURY CAUSED BY HAZARDOUS SUBSTANCES		N/A
7.2	Reduction of exposure to hazardous substances		N/A
7.3	Ozone exposure		N/A
7.4	Use of personal safeguards (PPE)		N/A
	Personal safeguards and instructions	---	—
7.5	Use of instructional safeguards and instructions		N/A
	Instructional safeguard (ISO 7010).....	---	—

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
7.6	Batteries.....:	(See Annex M)	N/A
8	MECHANICALLY-CAUSED INJURY		P
8.1	General		P
8.2	Mechanical energy source classifications	MS1: Fixed device, ≤ 2 m	P
8.3	Safeguards against mechanical energy sources		N/A
8.4	Safeguards against parts with sharp edges and corners		N/A
8.4.1	Safeguards		N/A
8.5	Safeguards against moving parts	No moving parts	N/A
8.5.1	MS2 or MS3 part required to be accessible for the function of the equipment		N/A
8.5.2	Instructional Safeguard..... :	---	—
8.5.4	Special categories of equipment comprising moving parts		N/A
8.5.4.1	Large data storage equipment		N/A
8.5.4.2	Equipment having electromechanical device for destruction of media		N/A
8.5.4.2.1	Safeguards and Safety Interlocks	(See Annex F.4 and Annex K)	N/A
8.5.4.2.2	Instructional safeguards against moving parts		N/A
	Instructional Safeguard.....:	---	—
8.5.4.2.3	Disconnection from the supply		N/A
8.5.4.2.4	Probe type and force (N)	---	N/A
8.5.5	High Pressure Lamps		N/A
8.5.5.1	Energy Source Classification		N/A
8.5.5.2	High Pressure Lamp Explosion Test.....:	(See appended table 8.5.5.2)	N/A
8.6	Stability	Fixed device	N/A
8.6.1	Product classification		N/A
	Instructional Safeguard.....:	---	—
8.6.2	Static stability		N/A
8.6.2.2	Static stability test		N/A
	Applied Force..... :	---	—
8.6.2.3	Downward Force Test		N/A
8.6.3	Relocation stability test		N/A
	Unit configuration during 10° tilt	---	—
8.6.4	Glass slide test		N/A
8.6.5	Horizontal force test (Applied Force)	---	N/A
	Position of feet or movable parts..... :	---	—
8.7	Equipment mounted to wall or ceiling		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
8.7.1	Mounting Means (Length of screws (mm) and mounting surface)	---	N/A
8.7.2	Direction and applied force	---	N/A
8.8	Handles strength		N/A
8.8.1	Classification		N/A
8.8.2	Applied Force	---	N/A
8.9	Wheels or casters attachment requirements		N/A
8.9.1	Classification		N/A
8.9.2	Applied force	---	—
8.10	Carts, stands and similar carriers		N/A
8.10.1	General		N/A
8.10.2	Marking and instructions		N/A
	Instructional Safeguard.....	---	—
8.10.3	Cart, stand or carrier loading test and compliance		N/A
	Applied force	---	—
8.10.4	Cart, stand or carrier impact test		N/A
8.10.5	Mechanical stability		N/A
	Applied horizontal force (N).....	---	—
8.10.6	Thermoplastic temperature stability (°C)	---	N/A
8.11	Mounting means for rack mounted equipment		N/A
8.11.1	General		N/A
8.11.2	Product Classification		N/A
8.11.3	Mechanical strength test, variable <i>N</i>	---	N/A
8.11.4	Mechanical strength test 250N, including end stops	---	N/A
8.12	Telescoping or rod antennas.....	(See Annex T)	N/A
	Button/Ball diameter (mm).....	---	—
9	THERMAL BURN INJURY		P
9.2	Thermal energy source classifications	TS1: Accessible surfaces	P
9.3	Safeguard against thermal energy sources		N/A
9.4	Requirements for safeguards		N/A
9.4.1	Equipment safeguard		N/A
9.4.2	Instructional safeguard	---	N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
10	RADIATION		P
10.2	Radiation energy source classification	RS1: LED indicators	P
10.2.1	General classification		P
10.3	Protection against laser radiation		N/A
	Laser radiation that exists equipment:		—
	Normal, abnormal, single-fault..... :	---	N/A
	Instructional safeguard :	---	—
	Tool :	---	—
10.4	Protection against visible, infrared, and UV radiation		N/A
10.4.1	General		N/A
10.4.1.a)	RS3 for Ordinary and instructed persons :	---	N/A
10.4.1.b)	RS3 accessible to a skilled person :	---	N/A
	Personal safeguard (PPE) instructional safeguard :	---	—
10.4.1.c)	Equipment visible, IR, UV does not exceed RS1 :		N/A
10.4.1.d)	Normal, abnormal, single-fault conditions :	(See appended table B.3 & B.4)	N/A
10.4.1.e)	Enclosure material employed as safeguard is opaque :	---	N/A
10.4.1.f)	UV attenuation :	---	N/A
10.4.1.g)	Materials resistant to degradation UV :	---	N/A
10.4.1.h)	Enclosure containment of optical radiation..... :	---	N/A
10.4.1.i)	Exempt Group under normal operating conditions :	---	N/A
10.4.2	Instructional safeguard :	---	N/A
10.5	Protection against x-radiation		N/A
10.5.1	X- radiation energy source that exists equipment :	(See appended table B.3 & B.4)	N/A
	Normal, abnormal, single fault conditions		N/A
	Equipment safeguards..... :	---	N/A
	Instructional safeguard for skilled person :	---	N/A
10.5.3	Most unfavourable supply voltage to give maximum radiation :	---	—
	Abnormal and single-fault condition..... :	(See appended table B.3 & B.4)	N/A
	Maximum radiation (pA/kg)..... :	---	N/A
10.6	Protection against acoustic energy sources		N/A
10.6.1	General		N/A
10.6.2	Classification		N/A
	Acoustic output, dB(A) :	---	N/A
	Output voltage, unweighted r.m.s. :	---	N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
10.6.4	Protection of persons		N/A
	Instructional safeguards.....:	---	N/A
	Equipment safeguard prevent ordinary person to RS2	---	—
	Means to actively inform user of increase sound pressure	---	—
	Equipment safeguard prevent ordinary person to RS2	---	—
10.6.5	Requirements for listening devices (headphones, earphones, etc.)		N/A
10.6.5.1	Corded passive listening devices with analog input		N/A
	Input voltage with 94 dB(A) L_{Aeq} acoustic pressure output	---	—
10.6.5.2	Corded listening devices with digital input		N/A
	Maximum dB(A)	---	—
10.6.5.3	Cordless listening device		N/A
	Maximum dB(A)	---	—
B	NORMAL OPERATING CONDITION TESTS, ABNORMAL OPERATING CONDITION TESTS AND SINGLE FAULT CONDITION TESTS		P
B.2	Normal Operating Conditions		P
B.2.1	General requirements	(See Test Item Particulars and appended test tables)	P
	Audio Amplifiers and equipment with audio amplifiers.....:	(See Annex E)	N/A
B.2.3	Supply voltage and tolerances		P
B.2.5	Input test	(See appended table B.2.5)	P
B.3	Simulated abnormal operating conditions		P
B.3.1	General requirements	(See appended table B.3)	P
B.3.2	Covering of ventilation openings		N/A
B.3.3	D.C. mains polarity test	Coded plug	N/A
B.3.4	Setting of voltage selector	No such parts	N/A
B.3.5	Maximum load at output terminals.....:	USB (X1300)	P
B.3.6	Reverse battery polarity	No battery	N/A
B.3.7	Abnormal operating conditions as specified in Clause E.2.		N/A
B.3.8	Safeguards functional during and after abnormal operating conditions		P
B.4	Simulated single fault conditions		P
B.4.2	Temperature controlling device open or short-circuited.....:	(See appended table B.4)	N/A
B.4.3	Motor tests		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
B.4.3.1	Motor blocked or rotor locked increasing the internal ambient temperature	(See Clause G.5)	N/A
B.4.4	Short circuit of functional insulation		P
B.4.4.1	Short circuit of clearances for functional insulation		P
B.4.4.2	Short circuit of creepage distances for functional insulation		P
B.4.4.3	Short circuit of functional insulation on coated printed boards		N/A
B.4.5	Short circuit and interruption of electrodes in tubes and semiconductors		N/A
B.4.6	Short circuit or disconnect of passive components		P
B.4.7	Continuous operation of components		P
B.4.8	Class 1 and Class 2 energy sources within limits during and after single fault conditions		P
B.4.9	Battery charging under single fault conditions.....	No battery (See Annex M)	N/A
C	UV RADIATION		N/A
C.1	Protection of materials in equipment from UV radiation		N/A
C.1.2	Requirements		N/A
C.1.3	Test method		N/A
C.2	UV light conditioning test		N/A
C.2.1	Test apparatus		N/A
C.2.2	Mounting of test samples		N/A
C.2.3	Carbon-arc light-exposure apparatus		N/A
C.2.4	Xenon-arc light exposure apparatus		N/A
D	TEST GENERATORS		N/A
D.1	Impulse test generators		N/A
D.2	Antenna interface test generator		N/A
D.3	Electronic pulse generator		N/A
E	TEST CONDITIONS FOR EQUIPMENT CONTAINING AUDIO AMPLIFIERS		N/A
E.1	Audio amplifier normal operating conditions		N/A
	Audio signal voltage (V)	---	---
	Rated load impedance (Ω)	---	---
E.2	Audio amplifier abnormal operating conditions		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
F	EQUIPMENT MARKINGS, INSTRUCTIONS, AND INSTRUCTIONAL SAFEGUARDS		P
F.1	General requirements		P
	Instructions – Language :	English	—
F.2	Letter symbols and graphical symbols		P
F.2.1	Letter symbols according to IEC60027-1		P
F.2.2	Graphic symbols IEC, ISO or manufacturer specific	See marking plate	P
F.3	Equipment markings		P
F.3.1	Equipment marking locations		P
F.3.2	Equipment identification markings		P
F.3.2.1	Manufacturer identification :	NetModule	—
F.3.2.2	Model identification :	NB800	—
F.3.3	Equipment rating markings		P
F.3.3.1	Equipment with direct connection to mains	No mains	N/A
F.3.3.2	Equipment without direct connection to mains		P
F.3.3.3	Nature of supply voltage :	==	—
F.3.3.4	Rated voltage..... :	12 - 24 V==	—
F.3.3.4	Rated frequency :	---	—
F.3.3.6	Rated current or rated power..... :	0.4 A / 5 W	—
F.3.3.7	Equipment with multiple supply connections		N/A
F.3.4	Voltage setting device		N/A
F.3.5	Terminals and operating devices		P
F.3.5.1	Mains appliance outlet and socket-outlet markings :	---	N/A
F.3.5.2	Switch position identification marking..... :	---	N/A
F.3.5.3	Replacement fuse identification and rating markings :	Not replaceable by user	N/A
F.3.5.4	Replacement battery identification marking..... :	---	N/A
F.3.5.5	Terminal marking location		P
F.3.6	Equipment markings related to equipment classification		N/A
F.3.6.1	Class I Equipment		N/A
F.3.6.1.1	Protective earthing conductor terminal		N/A
F.3.6.1.2	Neutral conductor terminal		N/A
F.3.6.1.3	Protective bonding conductor terminals		N/A
F.3.6.2	Class II equipment (IEC60417-5172)		N/A
F.3.6.2.1	Class II equipment with or without functional earth		N/A
F.3.6.2.2	Class II equipment with functional earth terminal marking		N/A
F.3.7	Equipment IP rating marking :	---	—

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
F.3.8	External power supply output marking		N/A
F.3.9	Durability, legibility and permanence of marking		P
F.3.10	Test for permanence of markings		P
F.4	Instructions		P
	a) Equipment for use in locations where children not likely to be present - marking		N/A
	b) Instructions given for installation or initial use		P
	c) Equipment intended to be fastened in place		P
	d) Equipment intended for use only in restricted access area		N/A
	e) Audio equipment terminals classified as ES3 and other equipment with terminals marked in accordance F.3.6.1		N/A
	f) Protective earthing employed as safeguard		N/A
	g) Protective earthing conductor current exceeding ES 2 limits		N/A
	h) Symbols used on equipment	See marking plate	P
	i) Permanently connected equipment not provided with all-pole mains switch		N/A
j)	j) Replaceable components or modules providing safeguard function		N/A
F.5	Instructional safeguards		N/A
	Where "instructional safeguard" is referenced in the test report it specifies the required elements, location of marking and/or instruction		N/A
G	COMPONENTS		P
G.1	Switches		N/A
G.1.1	General requirements		N/A
G.1.2	Ratings, endurance, spacing, maximum load		N/A
G.2	Relays		P
G.2.1	General requirements	EN 61810-1	P
G.2.2	Overload test		P
G.2.3	Relay controlling connectors supply power		N/A
G.2.4	Mains relay, modified as stated in G.2		N/A
G.3	Protection Devices		P
G.3.1	Thermal cut-offs		N/A
G.3.1.1a) &b)	Thermal cut-outs separately approved according to IEC 60730 with conditions indicated in a) & b)		N/A
G.3.1.1c)	Thermal cut-outs tested as part of the equipment as indicated in c)		N/A
G.3.1.2	Thermal cut-off connections maintained and secure		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
G.3.2	Thermal links		N/A
G.3.2.1a)	Thermal links separately tested with IEC 60691		N/A
G.3.2.1b)	Thermal links tested as part of the equipment		N/A
	Aging hours (H)..... :	---	—
	Single Fault Condition..... :	---	—
	Test Voltage (V) and Insulation Resistance (Ω) . :	---	—
G.3.3	PTC Thermistors		P
G.3.4	Overcurrent protection devices		N/A
G.3.5	Safeguards components not mentioned in G.3.1 to G.3.5		N/A
G.3.5.1	Non-resettable devices suitably rated and marking provided	Not replaceable by user	N/A
G.3.5.2	Single faults conditions :	(See appended Table B.4)	N/A
G.4	Connectors		P
G.4.1	Spacings		P
G.4.2	Mains connector configuration :	No mains	N/A
G.4.3	Plug is shaped that insertion into mains socket-outlets or appliance coupler is unlikely		N/A
G.5	Wound Components		N/A
G.5.1	Wire insulation in wound components	(See Annex J)	N/A
G.5.1.2 a)	Two wires in contact inside wound component, angle between 45° and 90°		N/A
G.5.1.2 b)	Construction subject to routine testing		N/A
G.5.2	Endurance test on wound components		N/A
G.5.2.1	General test requirements		N/A
G.5.2.2	Heat run test		N/A
	Time (s)..... :	---	—
	Temperature (°C)..... :	---	—
G.5.2.3	Wound Components supplied by mains		N/A
G.5.3	Transformers		N/A
G.5.3.1	Requirements applied (IEC61204-7, IEC61558-1/-2, and/or IEC62368-1)	---	N/A
	Position	---	—
	Method of protection	---	—
G.5.3.2	Insulation		N/A
	Protection from displacement of windings	---	—
G.5.3.3	Overload test..... :	(See appended table B.3)	N/A
G.5.3.3.1	Test conditions		N/A
G.5.3.3.2	Winding Temperatures testing in the unit		N/A
G.5.3.3.3	Winding Temperatures - Alternative test method		N/A
G.5.4	Motors		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
G.5.4.1	General requirements		N/A
	Position	---	---
G.5.4.2	Test conditions		N/A
G.5.4.3	Running overload test		N/A
G.5.4.4	Locked-rotor overload test		N/A
	Test duration (days)	---	---
G.5.4.5	Running overload test for d.c. motors in secondary circuits		N/A
G.5.4.5.2	Tested in the unit		N/A
	Electric strength test (V)	---	---
G.5.4.5.3	Tested on the Bench - Alternative test method; test time (h)	---	N/A
	Electric strength test (V)	---	---
G.5.4.6	Locked-rotor overload test for d.c. motors in secondary circuits		N/A
G.5.4.6.2	Tested in the unit		N/A
	Maximum Temperature	---	N/A
	Electric strength test (V)	---	N/A
G.5.4.6.3	Tested on the bench - Alternative test method; test time (h)	---	N/A
	Electric strength test (V)	---	N/A
G.5.4.7	Motors with capacitors		N/A
G.5.4.8	Three-phase motors		N/A
G.5.4.9	Series motors		N/A
	Operating voltage	---	---
G.6	Wire Insulation		N/A
G.6.1	General		N/A
G.6.2	Solvent-based enamel wiring insulation		N/A
G.7	Mains supply cords		N/A
G.7.1	General requirements	No mains	N/A
	Type	---	---
	Rated current (A)	---	---
	Cross-sectional area (mm ²), (AWG)	---	---
G.7.2	Compliance and test method		N/A
G.7.3	Cord anchorages and strain relief for non-detachable power supply cords		N/A
G.7.3.2	Cord strain relief		N/A
G.7.3.2.1	Requirements		N/A
	Strain relief test force (N)	---	---
G.7.3.2.2	Strain relief mechanism failure		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
G.7.3.2.3	Cord sheath or jacket position, distance (mm) ... :	---	—
G.7.3.2.4	Strain relief comprised of polymeric material		N/A
G.7.4	Cord Entry..... :	(See appended table 5.4.11.1)	N/A
G.7.5	Non-detachable cord bend protection		N/A
G.7.5.1	Requirements		N/A
G.7.5.2	Mass (g) :	---	—
	Diameter (m)..... :	---	—
	Temperature (°C)..... :	---	—
G.7.6	Supply wiring space		N/A
G.7.6.2	Stranded wire		N/A
G.7.6.2.1	Test with 8 mm strand		N/A
G.8	Varistors		N/A
G.8.1	General requirements		N/A
G.8.2	Safeguard against shock		N/A
G.8.3	Safeguard against fire		N/A
G.8.3.2	Varistor overload test..... :	(See appended table B.3)	N/A
G.8.3.3	Temporary overvoltage..... :	(See appended table B.3)	N/A
G.9	Integrated Circuit (IC) Current Limiters		N/A
G.9.1 a)	Manufacturer defines limit at max. 5A.		N/A
G.9.1 b)	Limiters do not have manual operator or reset		N/A
G.9.1 c)	Supply source does not exceed 250 VA :	---	—
G.9.1 d)	IC limiter output current (max. 5A)..... :	---	—
G.9.1 e)	Manufacturers' defined drift :	---	—
G.9.2	Test Program 1		N/A
G.9.3	Test Program 2		N/A
G.9.4	Test Program 3		N/A
G.10	Resistors		N/A
G.10.1	General requirements		N/A
G.10.2	Resistor test		N/A
G.10.3	Test for resistors serving as safeguards between the mains and an external circuit consisting of a coaxial cable		N/A
G.10.3.1	General requirements		N/A
G.10.3.2	Voltage surge test		N/A
G.10.3.3	Impulse test		N/A
G.11	Capacitor and RC units		N/A
G.11.1	General requirements		N/A
G.11.2	Conditioning of capacitors and RC units		N/A
G.11.3	Rules for selecting capacitors		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
G.12	Optocouplers		P
	Optocouplers comply with IEC 60747-5-5:2007 Spacing or Electric Strength Test (specify option and test results)	EN 60747-5-5	P
	Type test voltage Vini	3'750 VAC	—
	Routine test voltage, Vini,b	---	—
G.13	Printed boards		P
G.13.1	General requirements		P
G.13.2	Uncoated printed boards		P
G.13.3	Coated printed boards		N/A
G.13.4	Insulation between conductors on the same inner surface		P
	Compliance with cemented joint requirements (Specify construction)	---	—
G.13.5	Insulation between conductors on different surfaces		N/A
	Distance through insulation	(See appended table 5.4.4.5)	N/A
	Number of insulation layers (pcs)	---	—
G.13.6	Tests on coated printed boards		N/A
G.13.6.1	Sample preparation and preliminary inspection		N/A
G.13.6.2a)	Thermal conditioning		N/A
G.13.6.2b)	Electric strength test		N/A
G.13.6.2c)	Abrasion resistance test		N/A
G.14	Coating on components terminals		N/A
G.14.1	Requirements	(See G.13)	N/A
G.15	Liquid filled components		N/A
G.15.1	General requirements		N/A
G.15.2	Requirements		N/A
G.15.3	Compliance and test methods		N/A
G.15.3.1	Hydrostatic pressure test		N/A
G.15.3.2	Creep resistance test		N/A
G.15.3.3	Tubing and fittings compatibility test		N/A
G.15.3.4	Vibration test		N/A
G.15.3.5	Thermal cycling test		N/A
G.15.3.6	Force test		N/A
G.15.4	Compliance		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
G.16	IC including capacitor discharge function (ICX)		N/A
a)	Humidity treatment in accordance with sc5.4.8 – 120 hours		N/A
b)	Impulse test using circuit 2 with $U_c =$ to transient voltage	---	N/A
C1)	Application of ac voltage at 110% of rated voltage for 2.5 minutes		N/A
C2)	Test voltage	---	—
D1)	10,000 cycles on and off using capacitor with smallest capacitance resistor with largest resistance specified by manufacturer		N/A
D2)	Capacitance	---	—
D3)	Resistance	---	—
H	CRITERIA FOR TELEPHONE RINGING SIGNALS		N/A
H.1	General		N/A
H.2	Method A		N/A
H.3	Method B		N/A
H.3.1	Ringing signal		N/A
H.3.1.1	Frequency (Hz)	---	—
H.3.1.2	Voltage (V)	---	—
H.3.1.3	Cadence; time (s) and voltage (V)	---	—
H.3.1.4	Single fault current (mA):	---	—
H.3.2	Tripping device and monitoring voltage	---	N/A
H.3.2.1	Conditions for use of a tripping device or a monitoring voltage complied with		N/A
H.3.2.2	Tripping device		N/A
H.3.2.3	Monitoring voltage (V)	---	—
J	INSULATED WINDING WIRES FOR USE WITHOUT INTERLEAVED INSULATION		N/A
	General requirements	(See separate test report)	N/A
K	SAFETY INTERLOCKS		N/A
K.1	General requirements		N/A
K.2	Components of safety interlock safeguard mechanism	(See Annex G)	N/A
K.3	Inadvertent change of operating mode		N/A
K.4	Interlock safeguard override		N/A
K.5	Fail-safe		N/A
	Compliance	(See appended table B.4)	N/A
K.6	Mechanically operated safety interlocks		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
K.6.1	Endurance requirement		N/A
K.6.2	Compliance and Test method..... :	---	N/A
K.7	Interlock circuit isolation		N/A
K.7.1	Separation distance for contact gaps & interlock circuit elements (type and circuit location) :	---	N/A
K.7.2	Overload test, Current (A)..... :	---	N/A
K.7.3	Endurance test		N/A
K.7.4	Electric strength test :	(See appended table 5.4.11)	N/A
L	DISCONNECT DEVICES		P
L.1	General requirements	Plug	P
L.2	Permanently connected equipment		N/A
L.3	Parts that remain energized		N/A
L.4	Single phase equipment		N/A
L.5	Three-phase equipment		N/A
L.6	Switches as disconnect devices		N/A
L.7	Plugs as disconnect devices		P
L.8	Multiple power sources		N/A
M	EQUIPMENT CONTAINING BATTERIES AND THEIR PROTECTION CIRCUITS		N/A
M.1	General requirements		N/A
M.2	Safety of batteries and their cells		N/A
M.2.1	Requirements		N/A
M.2.2	Compliance and test method (identify method).. :	---	N/A
M.3	Protection circuits		N/A
M.3.1	Requirements		N/A
M.3.2	Tests		N/A
	- Overcharging of a rechargeable battery		N/A
	- Unintentional charging of a non-rechargeable battery		N/A
	- Reverse charging of a rechargeable battery		N/A
	- Excessive discharging rate for any battery		N/A
M.3.3	Compliance :	(See appended Tables and Annex M and M.4)	N/A
M.4	Additional safeguards for equipment containing secondary lithium battery		N/A
M.4.1	General		N/A
M.4.2	Charging safeguards		N/A
M.4.2.1	Charging operating limits		N/A
M.4.2.2a)	Charging voltage, current and temperature..... :	(See Table M.4)	—

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
M.4.2.2 b)	Single faults in charging circuitry	(See Annex B.4)	—
M.4.3	Fire Enclosure		N/A
M.4.4	Endurance of equipment containing a secondary lithium battery		N/A
M.4.4.2	Preparation		N/A
M.4.4.3	Drop and charge/discharge function tests		N/A
	Drop		N/A
	Charge		N/A
	Discharge		N/A
M.4.4.4	Charge-discharge cycle test		N/A
M.4.4.5	Result of charge-discharge cycle test		N/A
M.5	Risk of burn due to short circuit during carrying		N/A
M.5.1	Requirement		N/A
M.5.2	Compliance and Test Method (Test of P.2.3)		N/A
M.6	Prevention of short circuits and protection from other effects of electric current		N/A
M.6.1	Short circuits		N/A
M.6.1.1	General requirements		N/A
M.6.1.2	Test method to simulate an internal fault		N/A
M.6.1.3	Compliance (Specify M.6.1.2 or alternative method)	---	N/A
M.6.2	Leakage current (mA)	---	N/A
M.7	Risk of explosion from lead acid and NiCd batteries		N/A
M.7.1	Ventilation preventing explosive gas concentration		N/A
M.7.2	Compliance and test method		N/A
M.8	Protection against internal ignition from external spark sources of lead acid batteries		N/A
M.8.1	General requirements		N/A
M.8.2	Test method		N/A
M.8.2.1	General requirements		N/A
M.8.2.2	Estimation of hypothetical volume V_z (m ³ /s)	---	—
M.8.2.3	Correction factors.....	---	—
M.8.2.4	Calculation of distance d (mm)	---	—
M.9	Preventing electrolyte spillage		N/A
M.9.1	Protection from electrolyte spillage		N/A
M.9.2	Tray for preventing electrolyte spillage		N/A
M.10	Instructions to prevent reasonably foreseeable misuse (Determination of compliance: inspection, data review; or abnormal testing)	---	N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
N	ELECTROCHEMICAL POTENTIALS		P
	Metal(s) used	Aluminum/stainless steel	—
O	MEASUREMENT OF CREEPAGE DISTANCES AND CLEARANCES		P
	Figures O.1 to O.20 of this Annex applied.....	---	—
P	SAFEGUARDS AGAINST ENTRY OF FOREIGN OBJECTS AND SPILLAGE OF INTERNAL LIQUIDS		P
P.1	General requirements		P
P.2.2	Safeguards against entry of foreign object		P
	Location and Dimensions (mm)	No openings, without SIM cover only small SIM card slots, can't be entry	—
P.2.3	Safeguard against the consequences of entry of foreign object		N/A
P.2.3.1	Safeguards against the entry of a foreign object		N/A
	Openings in transportable equipment		N/A
	Transportable equipment with metalized plastic parts	---	N/A
P.2.3.2	Openings in transportable equipment in relation to metallized parts of a barrier or enclosure (identification of supplementary safeguard)	---	N/A
P.3	Safeguards against spillage of internal liquids	No internal liquids	N/A
P.3.1	General requirements		N/A
P.3.2	Determination of spillage consequences		N/A
P.3.3	Spillage safeguards		N/A
P.3.4	Safeguards effectiveness		N/A
P.4	Metallized coatings and adhesive securing parts		N/A
P.4.2 a)	Conditioning testing		N/A
	Tc (°C).....	---	—
	Tr (°C)	---	—
	Ta (°C)	---	—
P.4.2 b)	Abrasion testing	(See G.13.6.2)	N/A
P.4.2 c)	Mechanical strength testing	(See Annex T)	N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
Q	CIRCUITS INTENDED FOR INTERCONNECTION WITH BUILDING WIRING		N/A
Q.1	Limited power sources		N/A
Q.1.1 a)	Inherently limited output		N/A
Q.1.1 b)	Impedance limited output		N/A
	- Regulating network limited output under normal operating and simulated single fault condition		N/A
Q.1.1 c)	Overcurrent protective device limited output		N/A
Q.1.1 d)	IC current limiter complying with G.9		N/A
Q.1.2	Compliance and test method		N/A
Q.2	Test for external circuits – paired conductor cable		N/A
	Maximum output current (A) :	---	—
	Current limiting method..... :	---	—
R	LIMITED SHORT CIRCUIT TEST		N/A
R.1	General requirements		N/A
R.2	Determination of the overcurrent protective device and circuit		N/A
R.3	Test method Supply voltage (V) and short-circuit current (A). :	---	N/A
S	TESTS FOR RESISTANCE TO HEAT AND FIRE		N/A
S.1	Flammability test for fire enclosures and fire barrier materials of equipment where the steady state power does not exceed 4 000 W	Metal	N/A
	Samples, material :	---	—
	Wall thickness (mm) :	---	—
	Conditioning (°C) :	---	—
	Test flame according to IEC 60695-11-5 with conditions as set out		N/A
	- Material not consumed completely		N/A
	- Material extinguishes within 30s		N/A
	- No burning of layer or wrapping tissue		N/A
S.2	Flammability test for fire enclosure and fire barrier integrity		N/A
	Samples, material :	---	—
	Wall thickness (mm) :	---	—
	Conditioning (°C) :	---	—
	Test flame according to IEC 60695-11-5 with conditions as set out		N/A
	Test specimen does not show any additional hole		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
S.3	Flammability test for the bottom of a fire enclosure		N/A
	Samples, material	---	---
	Wall thickness (mm)	---	---
	Cheesecloth did not ignite		N/A
S.4	Flammability classification of materials		N/A
S.5	Flammability test for fire enclosures and fire barrier materials of equipment where the steady state power does not exceed 4 000 W		N/A
	Samples, material	---	---
	Wall thickness (mm)	---	---
	Conditioning (test condition), (°C).....	---	---
	Test flame according to IEC 60695-11-20 with conditions as set out		N/A
	After every test specimen was not consumed completely		N/A
	After fifth flame application, flame extinguished within 1 min		N/A
T	MECHANICAL STRENGTH TESTS		P
T.1	General requirements		P
T.2	Steady force test, 10 N	(See appended table T.2)	P
T.3	Steady force test, 30 N	(See appended table T.3)	P
T.4	Steady force test, 100 N	(See appended table T.4)	N/A
T.5	Steady force test, 250 N	(See appended table T.5)	P
T.6	Enclosure impact test	(See appended table T.6)	P
	Fall test		P
	Swing test		N/A
T.7	Drop test	Fixed device (See appended table T.7)	N/A
T.8	Stress relief test	(See appended table T.8)	N/A
T.9	Impact Test (glass)		N/A
T.9.1	General requirements		N/A
T.9.2	Impact test and compliance		N/A
	Impact energy (J).....	---	---
	Height (m)	---	---
T.10	Glass fragmentation test.....	(See sub-clause 4.4.4.9)	N/A
T.11	Test for telescoping or rod antennas		N/A
	Torque value (Nm)	---	---

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
U	MECHANICAL STRENGTH OF CATHODE RAY TUBES (CRT) AND PROTECTION AGAINST THE EFFECTS OF IMPLOSION		N/A
U.1	General requirements		N/A
U.2	Compliance and test method for non-intrinsically protected CRTs		N/A
U.3	Protective Screen:	(See Annex T)	N/A
V	DETERMINATION OF ACCESSIBLE PARTS (FINGERS, PROBES AND WEDGES)		P
V.1	Accessible parts of equipment	Enclosure & interface connectors	P
V.2	Accessible part criterion		P

4.1.2	TABLE: List of critical components					P
Object / part No.	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity ¹	
- Description ²⁾ :	NB800 Mainboard					
PCB NB800 Mainboard Rev. 2.1, Rev. 2.2	Kingboard Laminates Holdings Ltd or various	KB-6160 or various	FR-4 1.6 mm 130 °C UL94 V-0	UL 746 CSA C22.2 No. 0.17	cURus E123995 or UL listed	
Connector X1200	Phoenix Contact GmbH & Co	MC 1.5/ 2-G- 3.5	160 V, 8 A 2-pol.	UL 1059 CSA C22.2 No. 158	VDE 40011723 CB DE1- 56063-B1B2 cURus E60425	
	Sauro SRL	CTM-029P8	130 V, 11 A 8-pol.	UL 1059 CSA C22.2 No. 158	VDE 40013398 cURus E167473	
Resettable fuse Fi1400	Bel Fuse Inc	0ZCF Series 0ZCF0185FF2 C	Ih: 1.85 A, Itrip: 3.7 A, 33 V	EN 60738-1-1 UL 1434 CSA-C22.2 No.72	TÜV R50102117 cURus E305051	
Transient voltage suppressor D1400	Taiwan Semiconductor Co Ltd	SMCJ30CA	Bidirectional, 30 V	UL1557	UR E326243	
	Pan Jit Electronics Co Ltd	SMCJ30CA	Bidirectional, 30 V	UL 497B	UR E210467	
Capacitor C1403	Murata	GRM31BR73 A472KW01L	4.7 nF 1'000 VDC	IEC/EN 62368-1	Tested in appliance	
Ethernet connector T850-1A, T850-2A	Abracon LLC	ARJC02- 111009D	10/100Base-T IEEE 802.3 1'500 VAC	IEC/EN 62368-1	Tested in appliance	
- Description ²⁾ :	COM_IO Module					
Opto coupler U301	Toshiba Electronic Devices & Storage Corporation	TLP293GB	3'750 VAC	EN 60747-5-5 UL 1577	VDE cURus E67349	
Relay K400	EM Devices Corporation	EC2 5V	110 VDC, 2 A 60 W 1'500 VAC	EN 61810-1 UL 508 CSA-C22.2 No. 14-13	TÜV R9751153 UR E73266 CSA LR46266	
- Description ²⁾ :	Other components					
WWAN module	Huawei Technologies	ME909s-120	compliant with communication standards	LTE, WCDMA/HSDPA /HSUPA/HSPA+, GSM/GPRS/ EDGE	CE0682 FCC	

4.1.2	TABLE: List of critical components					P
Object / part No.	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity ¹	
	Huawei Technologies	MU709s-2	compliant with communication standards	WCDMA/HSDPA /HSUPA/HSPA+, GSM/GPRS/ EDGE	CE0682 FCC	
WLAN module	Texas Instruments	WL1837MOD	compliant with communication standards	EN 60950-1 Dual-band IEEE 802.11	CE FCC	
Enclosure	NetModule AG	NB800 IP40	Aluminium min. 1.4	IEC/EN 62368-1	Tested in appliance	
Supplementary information: ¹⁾ Provided evidence ensures the agreed level of compliance. See OD-CB2039. ²⁾ Description line content is optional. Main line description needs to clearly detail the component used for testing						

4.8.4, 4.8.5	TABLE: Lithium coin/button cell batteries mechanical tests			N/A
(The following mechanical tests are conducted in the sequence noted.)				
4.8.4.2	TABLE: Stress Relief test			—
Part		Material	Oven Temperature (°C)	Comments
4.8.4.3	TABLE: Battery replacement test			—
Battery part no.			—	
Battery Installation/withdrawal		Battery Installation/Removal Cycle		Comments
		1		
		2		
		3		
		4		
		5		
		6		
		8		
		9		
		10		
4.8.4.4	TABLE: Drop test			—
Impact Area		Drop Distance	Drop No.	Observations
			1	
			2	
			3	
4.8.4.5	TABLE: Impact			—
Impacts per surface		Surface tested	Impact energy (Nm)	Comments

4.8.4, 4.8.5	TABLE: Lithium coin/button cell batteries mechanical tests			N/A
(The following mechanical tests are conducted in the sequence noted.)				
4.8.4.6	TABLE: Crush test			—
Test position		Surface tested	Crushing Force (N)	Duration force applied (s)
Supplementary information:				

4.8.5	TABLE: Lithium coin/button cell batteries mechanical test result			N/A
Test position		Surface tested	Force (N)	Duration force applied (s)
Supplementary information:				

5.2	Table: Classification of electrical energy sources						P
5.2.2.2 – Steady State Voltage and Current conditions							
No.	Supply Voltage	Location (e.g. circuit designation)	Test conditions	Parameters			ES Class
				U (Vrms or Vpk)	I (A _{pk} or A _{rms})	Hz	
1	28.8 VDC	Power input circuits	Normal	28.8 VDC	---	---	ES1
			Abnormal	28.8 VDC	---	---	
			Single fault – OC/SC	28.8 VDC / 0 VDC	---	---	
2	28.8 VDC	+5V0 (C1410, C1411)	Normal	5.07 VDC	---	---	ES1
			Abnormal	5.07 VDC	---	---	
			Single fault – OC/SC	5.07 VDC / 0 VDC	---	---	
3	28.8 VDC	+5V0_USB (C1418, C1421)	Normal	5.07 VDC	---	---	ES1
			Abnormal	5.07 VDC	---	---	
			Single fault – OC/SC	5.07 VDC / 0 VDC	---	---	

5.2.2.3 - Capacitance Limits							
No.	Supply Voltage	Location (e.g. circuit designation)	Test conditions	Parameters		ES Class	
				Capacitance, nF	Upk (V)		
---	---	---	Normal	---	---	---	
			Abnormal	---	---		
			Single fault – SC/OC	---	---		
5.2.2.4 - Single Pulses							
No.	Supply Voltage	Location (e.g. circuit designation)	Test conditions	Parameters			ES Class
				Duration (ms)	Upk (V)	Ipk (mA)	
---	---	---	Normal	---	---	---	---
			Abnormal	---	---	---	
			Single fault – SC/OC	---	---	---	
5.2.2.5 - Repetitive Pulses							
No.	Supply Voltage	Location (e.g. circuit designation)	Test conditions	Parameters			ES Class
				Off time (ms)	Upk (V)	Ipk (mA)	
---	---	---	Normal	---	---	---	---
			Abnormal	---	---	---	
			Single fault – SC/OC	---	---	---	
Test Conditions: Normal – Abnormal - Supplementary information: SC=Short Circuit, OC=Open Circuit							

5.4.1.4, 6.3.2, 9.0, B.2.6	TABLE: Temperature measurements						P
	Supply voltage (V)	28.8 VDC	---	---	---	---	
	Ambient T _{min} (°C)	24.7	---	---	---	---	
	Ambient T _{max} (°C)	24.9	---	---	---	---	
	Tma (°C)	70	---	---	---	---	
Maximum measured temperature T of part/at:		T (°C)				Allowed T _{max} (°C)	
Surface temperatures:							
Enclosure (near antenna connectors)		36.7	---	---	---	70	
Power connector		35.4	---	---	---	77	
Ethernet connector		36.8	---	---	---	60	
Component temperatures:							
Voltage converter N1400		52.8	---	---	---	---	
PCB		52.3	---	---	---	130	
Inner air temperature			---	---	---	---	
Supplementary information: Higher temperatures measured at a supply voltage of 28.8 VDC (in comparison with 9.6 VDC)							
Note: This test covers only safety aspects; functional failures due to the temperatures are not considered							
Temperature T of winding:	t ₁ (°C)	R ₁ (Ω)	t ₂ (°C)	R ₂ (Ω)	T (°C)	Allowed T _{max} (°C)	Insulation class
---	---	---	---	---	---	---	---
Supplementary information: Note 1: Tma should be considered as directed by applicable requirement Note 2: Tma is not included in assessment of Touch Temperatures (Clause 9)							

5.4.1.10.2	TABLE: Vicat softening temperature of thermoplastics		N/A
Penetration (mm)			—
Object/ Part No./Material	Manufacturer/t rademark	T softening (°C)	
supplementary information:			

5.4.1.10.3	TABLE: Ball pressure test of thermoplastics			N/A
Allowed impression diameter (mm)		≤ 2 mm		—
Object/Part No./Material	Manufacturer/trademark	Test temperature (°C)	Impression diameter (mm)	
Supplementary information:				

5.4.2.2, 5.4.2.4 and 5.4.3	TABLE: Minimum Clearances/Creepage distance							P
Clearance (cl) and creepage distance (cr) at/of/between:	Up (V)	U r.m.s. (V)	Frequency (kHz) ¹	Required cl (mm)	cl (mm) ²	Required ³ cr (mm)	cr (mm)	
+VIN to GND Power input before fuse Fi1400 Mainboard Rev. 2.1	500	28.8	---	0.26 ¹⁾	0.25 ²⁾	0.53	0.25 ²⁾	
+VIN to GND Power input before fuse Fi1400 Mainboard Rev. 2.2	500	28.8	---	0.26 ¹⁾	0.53	0.53	0.53	
Isolated COM_I/Os to internal circuits	707	36	---	0.26 ¹⁾	1.0	0.82 ³⁾	1.0	
Supplementary information: ¹⁾ For operating up to 4'000 m sea level (multiplication factor = 1.29) 0.2 mm * 1.29 = 0.258 mm => 0.26 mm clearance ²⁾ According to B.4.4 and instructions in "User Manual: 4.8 Installation of the Power Supply" ³⁾ Interpolated Note 1: Only for frequency above 30 kHz Note 2: See table 5.4.2.4 if this is based on electric strength test Note 3: Provide Material Group								

5.4.2.3	TABLE: Minimum Clearances distances using required withstand voltage			P
	Overvoltage Category (OV):			I
	Pollution Degree:			2
Clearance distanced between:		Required withstand voltage	Required cl (mm)	Measured cl (mm)
+VIN to GND Power input before fuse Fi1400 Mainboard Rev. 2.1		500 Vp	0.26 ¹⁾	0.25 ²⁾
+VIN to GND Power input before fuse Fi1400 Mainboard Rev. 2.2		500 Vp	0.26 ¹⁾	1.0
Isolated COM_I/Os to internal circuits		707 Vp	0.26 ¹⁾	1.0
Ethernet to enclosure (including USB, power supply)		1'500 Vp	0.65 ¹⁾	1.8
Supplementary information: ¹⁾ For operating up to 4'000 m sea level (multiplication factor = 1.29) 0.2 mm * 1.29 = 0.258 mm => 0.26 mm clearance 0.5 mm * 1.29 = 0.645 mm => 0.65 mm clearance ²⁾ According to B.4.4 and instructions in “User Manual: 4.8 Installation of the Power Supply”				

5.4.2.4	TABLE: Clearances based on electric strength test			N/A
Test voltage applied between:		Required cl (mm)	Test voltage (kV) peak/ r.m.s. / d.c.	Breakdown Yes / No
Supplementary information:				

5.4.4.2, 5.4.4.5 c) 5.4.4.9	TABLE: Distance through insulation measurements					N/A
Distance through insulation di at/of:	Peak voltage (V)	Frequency (kHz)	Material	Required DTI (mm)	DTI (mm)	
Supplementary information:						

5.4.9	TABLE: Electric strength tests			P
Test voltage applied between:		Voltage shape (AC, DC)	Test voltage (V)	Breakdown Yes / No
Functional:				
---		---	---	---
Basic/supplementary:				
+VIN to GND Power input before fuse Fi1400		DC	550 ¹⁾	No
Isolated COM_I/Os to internal circuits		DC	813 ²⁾	No
Ethernet to enclosure (including USB, power supply)		DC	1'725 ³⁾	No
Reinforced:				
---		---	---	---
Routine Tests:				
---		---	---	---
Supplementary information: ¹⁾ For operating up to 4'000 m sea level (< 1 mm; multiplication factor = 1.10) $500 \text{ V} * 1.10 = 550 \text{ V}$ ²⁾ For operating up to 4'000 m sea level (≥ 1 to < 10 mm; multiplication factor = 1.15) $707 \text{ V} * 1.15 = 813 \text{ V}$ ³⁾ For operating up to 4'000 m sea level (≥ 1 to < 10 mm; multiplication factor = 1.15) $1'500 \text{ V} * 1.15 = 1'725 \text{ V}$				

5.5.2.2	TABLE: Stored discharge on capacitors					N/A
Supply Voltage (V), Hz	Test Location	Operating Condition (N, S)	Switch position On or off	Measured Voltage (after 2 seconds)	ES Classification	
<p>Supplementary information:</p> <p>X-capacitors installed for testing are:</p> <p><input type="checkbox"/> bleeding resistor rating:</p> <p><input type="checkbox"/> ICX:</p> <p>Notes:</p> <p>A. Test Location:</p> <p>Phase to Neutral; Phase to Phase; Phase to Earth; and/or Neutral to Earth</p> <p>B. Operating condition abbreviations:</p> <p>N – Normal operating condition (e.g., normal operation, or open fuse); S – Single fault condition</p>						

5.6.6.2	TABLE: Resistance of protective conductors and terminations				N/A
Accessible part	Test current (A)	Duration (min)	Voltage drop (V)	Resistance (Ω)	
Supplementary information:					

5.7.2.2, 5.7.4	TABLE: Earthed accessible conductive part		N/A
Supply voltage			—
Location		Test conditions specified in 6.1 of IEC 60990 or Fault Condition No in IEC 60990 clause 6.2.2.1 through 6.2.2.8, except for 6.2.2.7	Touch current (mA)
		1	
		2*	
		3	
		4	
		5	
		6	
		8	
Supplementary Information:			
Notes: [1] Supply voltage is the anticipated maximum Touch Voltage [2] Earthed neutral conductor [Voltage differences less than 1% or more] [3] Specify method used for measurement as described in IEC 60990 sub-clause 4.3 [4] IEC60990, sub-clause 6.2.2.7, Fault 7 not applicable. [5] (*) IEC60990, sub-clause 6.2.2.2 is not applicable if switch or disconnect device (e.g., appliance coupler) provided.			

6.2.2	Table: Electrical power sources (PS) measurements for classification					P
Source	Description	Measurement	Max Power after 3 s	Max Power after 5 s ^{*)}	PS Classification	
A	Power input ₁₎	Power (W) :	288	---	PS3	
		V _A (V) :	28.8	---		
		I _A (A) :	10	---		
B	+5V0 (C1410, C1411)	Power (W) :	14.89	---	PS1	
		V _A (V) :	4.58	---		
		I _A (A) :	3.25	---		
C	+5V0_USB (C1418, C1421)	Power (W) :	14.89	---	PS1	
		V _A (V) :	4.58	---		
		I _A (A) :	3.25	---		
Supplementary Information: 1) See instructions in “User Manual: 4.8 Installation of the Power Supply” (*) Measurement taken only when limits at 3 seconds exceed PS1 limits						

6.2.3.1	Table: Determination of Potential Ignition Sources (Arcing PIS)				N/A
Location	Open circuit voltage After 3 s (V _p)	Measured r.m.s current (I _{rms})	Calculated value (V _p x I _{rms})	Arcing PIS? Yes / No	
Supplementary information:					
An Arcing PIS requires a minimum of 50 V (peak) a.c. or d.c. An Arcing PIS is established when the product of the open circuit voltage (V _p) and normal operating condition rms current (I _{rms}) is greater than 15.					

6.2.3.2	Table: Determination of Potential Ignition Sources (Resistive PIS)				P
Circuit Location (x-y)	Operating Condition (Normal / Describe Single Fault)	Measured wattage or VA During first 30 s (W / VA)	Measured wattage or VA After 30 s (W / VA)	Protective Circuit, Regulator, or PTC Operated? Yes / No (Comment)	Resistive PIS? Yes/No
Power input circuits	Normal	3.46	3.46	No	No
Power input circuits	Before fuse FI1400 trips	66.6	66.6	No	Yes
Power input ¹⁾ max. 8 A	C1403 shorted	230.4	230.4	No	Yes
Supplementary Information: ¹⁾ See instructions in “User Manual: 4.8 Installation of the Power Supply” A combination of voltmeter, VA and ammeter IA may be used instead of a wattmeter. If a separate voltmeter and ammeter are used, the product of (VA x IA) is used to determine Resistive PIS classification. A Resistive PIS: (a) dissipates more than 15 W, measured after 30 s of normal operation, <u>or</u> (b) under single fault conditions has either a power exceeding 100 W measured immediately after the introduction of the fault if electronic circuits, regulators or PTC devices are used, or has an available power exceeding 15 W measured 30 s after introduction of the fault.					

8.5.5	TABLE: High Pressure Lamp		N/A
Description		Values	Energy Source Classification
Lamp type..... :			—
Manufacturer :			—
Cat no. :			—
Pressure (cold) (MPa)..... :			MS_
Pressure (operating) (MPa) :			MS_
Operating time (minutes) :			—
Explosion method..... :			—
Max particle length escaping enclosure (mm) :			MS_
Max particle length beyond 1 m (mm) :			MS_
Overall result :			
Supplementary information:			

B.2.5	TABLE: Input test						P
U (V)	I (A)	I rated (A)	P (W)	P rated (W)	Fuse No	I fuse (A)	Condition/status
9.6	0.264	0.4	2.53	5	Fi1400	1.85	Data transfer via wireless modules
12.0	0.225	0.4	2.70	5	Fi1400	1.85	Data transfer via wireless modules
24.0	0.134	0.4	3.22	5	Fi1400	1.85	Data transfer via wireless modules
28.8	0.120	0.4	3.46	5	Fi1400	1.85	Data transfer via wireless modules
Supplementary information: Equipment may be have rated current or rated power or both. Both should be measured							

B.3		TABLE: Abnormal operating condition tests						P
Ambient temperature (°C)					25			—
Power source for EUT: Manufacturer, model/type, output rating ...					See below			—
Component No.	Abnormal Condition	Supply voltage, (V)	Test time (min)	Fuse no.	Fuse current, (A)	T-couple	Temp. (°C)	Observation
X1300	overload	28.8	30	---	---	---	---	Max. power: 0.5 A @ 4.7 V, powered by +5V0_USB, current limited by U1500, no hazard
Supplementary information: Test table is provided to record abnormal and fault conditions for all applicable energy sources including Thermal burn injury. Column "Abnormal/Fault." Specify if test condition by indicating "Abnormal" then the condition for a Clause B.3 test or "Single Fault" then the condition for Clause B.4.								

B.4	TABLE: Fault condition tests							P
Ambient temperature (°C)					25			—
Power source for EUT: Manufacturer, model/type, output rating ...					See below			—
Component No.	Fault Condition	Supply voltage, (V)	Test time (min)	Fuse no.	Fuse current, (A)	T-couple	Temp. (°C)	Observation
C1403	short circuit	28.8	---	---	---	--	--	Max. input current: 8 A, limited by external power supply or by an ext. fuse (see instructions in "User Manual"), no hazard
C1401, C1402	short circuit after fuse Fi1400	28.8	---	Fi 1400	1.85 A	--	--	Fuse Fi1400 trips, no hazard
C1410, C1411 (+5V0)	short circuit	28.8	---	---	---	--	--	Current limited and thermal protected voltage regulator N1400, no hazard
C1418, C1421 (+5V0_USB)	short circuit	28.8	---	---	---	--	--	Current limited and thermal protected voltage regulator N1401, no hazard
Supplementary information: If no test time is declared test has not been carried out because considering the situation. All components within metallic enclosure without openings.								

Annex M	TABLE: Batteries								N/A	
The tests of Annex M are applicable only when appropriate battery data is not available								N/A		
Is it possible to install the battery in a reverse polarity position?							---		N/A	
	Non-rechargeable batteries			Rechargeable batteries						
	Discharging		Un-intentional charging	Charging		Discharging		Reversed charging		
	Meas. current	Manuf. Specs.		Meas. current	Manuf. Specs.	Meas. current	Manuf. Specs.	Meas. current	Manuf. Specs.	
Max. current during normal condition										
Max. current during fault condition										
Test results:									Verdict	
- Chemical leaks										
- Explosion of the battery										
- Emission of flame or expulsion of molten metal										
- Electric strength tests of equipment after completion of tests										
Supplementary information:										

Annex M.4	Table: Additional safeguards for equipment containing secondary lithium batteries					N/A
Battery/Cell No.	Test conditions	Measurements			Observation	
		U	I (A)	Temp (C)		
	Normal					
	Abnormal					
	Single fault –SC/OC					
	Normal					
	Abnormal					
	Single fault – SC/OC					
Supplementary Information:						

Battery identification	Charging at T_{lowest} (°C)	Observation	Charging at $T_{highest}$ (°C)	Observation
Supplementary Information:				

Annex Q.1	TABLE: Circuits intended for interconnection with building wiring (LPS)					N/A	
Note: Measured UOC (V) with all load circuits disconnected:							
Output Circuit	Components	U _{oc} (V)	I _{sc} (A)		S (VA)		
			Meas.	Limit	Meas.	Limit	
Supplementary Information: SC=Short circuit, OC=Open circuit							

T.2, T.3, T.4, T.5	TABLE: Steady force test					P
Part/Location	Material	Thickness (mm)	Force (N)	Test Duration (sec)	Observation	
Internal wire	PVC	---	10	5	No hazard	
Enclosure	Metal	Min. 1.4	30	5	No hazard	
Enclosure	Metal	Min. 1.4	250	5	No hazard	
Supplementary information:						

T.6, T.9	TABLE: Impact tests				P
Part/Location	Material	Thickness (mm)	Vertical distance (mm)	Observation	
Whole product	Metallic enclosure	Min. 1.4	1'300	No hazard	
Supplementary information:					

T.7	TABLE: Drop tests				N/A
Part/Location	Material	Thickness (mm)	Drop Height (mm)	Observation	
Supplementary information: Fixed device					

T.8	TABLE: Stress relief test					N/A
Part/Location	Material	Thickness (mm)	Oven Temperature (°C)	Duration (h)	Observation	
Supplementary information:						

List of test equipment used:

A completed list of used test equipment shall be provided in the Test Reports when a Manufacturer Testing Laboratory according to TMP/CTF stage 1 or WMT/CTF stage 2 procedure has been used.

Clause	Measurement / testing	Testing / measuring equipment / material used	Inventory no	Last calibration	Calibration due
all	Ambient conditions	PCE Deutschland GmbH, PCE-THB 40, Thermo-/Hygro-/Barometer	12.6632.12	03/2017	03/2018
5.2, 6.2, B.2.5, B.3, B.4	Electrical data, fault condition tests	Fluke, 189, Digital Multimeter	DV9771	10/2016	10/2017
5.2, 6.2, B.2.5, B.3, B.4	Electrical data, fault condition tests	Fluke, 189, Digital Multimeter	DV9772	12/2016	12/2017
5.2, 6.2, B.2.5, B.3, B.4	Electrical data, fault condition tests	Fluke, 87, Digital Multimeter	DV6681	12/2016	12/2017
5.4.2, 5.4.3	Clearances, creepage distances	Etalon, 0 - 150 mm, Caliper Gauge	M9702	07/2016	07/2017
5.4.1.4, 6.3.2, 9.0, B.2.6	Temperature measurements, fault condition tests	Fluke, 51, Digital Thermometer for K/J Thermocouples	DV9362	03/2017	03/2018
5.4.1.4, 6.3.2, 9.0, B.2.6	Temperature measurements, fault condition tests	Roth+Co, Typ K, Thermoelement Typ K (NiCr-Ni)	11.6632.01, 11.6632.02, 11.6632.03, 11.6632.04, 11.6632.05	12/2014	12/2017
5.4.9, 5.5.10	Electric strength tests	ETL, ATS400, High Voltage Tester	14.6632.03	07/2017 ¹⁾	07/2018 ¹⁾
T.6	Impact tests	Siemens, Impact Tester	MG5603	05/2014	05/2019
T.6	Impact tests	Futuro, Tri-Matic 3 m, Tape measure	12.6632.14	11/2015	11/2018

Measurements carried out between 03/2017 and 04/2017 as well as 12/2017 ¹⁾.

ATTACHMENT TO TEST REPORT IEC 62368-1 EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES (Audio/video, information and communication technology equipment Part 1: Safety requirements)	
Differences according to :	EN 62368-1:2014+A11:2017
Attachment Form No. :	EU_GD_IEC62368_1B_II
Attachment Originator :	Nemko AS
Master Attachment:	Date 2017-09-22
Copyright © 2017 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.	

IEC62368_1B - ATTACHMENT																																										
Clause	Requirement + Test			Result - Remark		Verdict																																				
	CENELEC COMMON MODIFICATIONS (EN)																																									
	Clauses, subclauses, notes, tables, figures and annexes which are additional to those in IEC 62368-1:2014 are prefixed “Z”.																																									
CONTENTS	Add the following annexes: Annex ZA (normative) Normative references to international publications with their corresponding European publications Annex ZB (normative) Special national conditions Annex ZC (informative) A-deviations Annex ZD (informative) IEC and CENELEC code designations for flexible cords																																									
	Delete all the “country” notes in the reference document (IEC 62368-1:2014) according to the following list: <table><tr><td>0.2.1</td><td>Note</td><td>1</td><td>Note 3</td><td>4.1.15</td><td>Note</td></tr><tr><td>4.7.3</td><td>Note 1 and 2</td><td>5.2.2.2</td><td>Note</td><td>5.4.2.3.2.2 Table 13</td><td>Note c</td></tr><tr><td>5.4.2.3.2.4</td><td>Note 1 and 3</td><td>5.4.2.5</td><td>Note 2</td><td>5.4.5.1</td><td>Note</td></tr><tr><td>5.5.2.1</td><td>Note</td><td>5.5.6</td><td>Note</td><td>5.6.4.2.1</td><td>Note 2 and 3</td></tr><tr><td>5.7.5</td><td>Note</td><td>5.7.6.1</td><td>Note 1 and 2</td><td>10.2.1 Table 39</td><td>Note 2, 3 and 4</td></tr><tr><td>10.5.3</td><td>Note 2</td><td>10.6.2.1</td><td>Note 3</td><td>F.3.3.6</td><td>Note 3</td></tr></table>					0.2.1	Note	1	Note 3	4.1.15	Note	4.7.3	Note 1 and 2	5.2.2.2	Note	5.4.2.3.2.2 Table 13	Note c	5.4.2.3.2.4	Note 1 and 3	5.4.2.5	Note 2	5.4.5.1	Note	5.5.2.1	Note	5.5.6	Note	5.6.4.2.1	Note 2 and 3	5.7.5	Note	5.7.6.1	Note 1 and 2	10.2.1 Table 39	Note 2, 3 and 4	10.5.3	Note 2	10.6.2.1	Note 3	F.3.3.6	Note 3	
0.2.1	Note	1	Note 3	4.1.15	Note																																					
4.7.3	Note 1 and 2	5.2.2.2	Note	5.4.2.3.2.2 Table 13	Note c																																					
5.4.2.3.2.4	Note 1 and 3	5.4.2.5	Note 2	5.4.5.1	Note																																					
5.5.2.1	Note	5.5.6	Note	5.6.4.2.1	Note 2 and 3																																					
5.7.5	Note	5.7.6.1	Note 1 and 2	10.2.1 Table 39	Note 2, 3 and 4																																					
10.5.3	Note 2	10.6.2.1	Note 3	F.3.3.6	Note 3																																					
	For special national conditions, see Annex ZB.																																									
1	Add the following note: NOTE Z1 The use of certain substances in electrical and electronic equipment is restricted within the EU: see Directive 2011/65/EU.					P																																				

IEC62368_1B - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
4.Z1	<p>Add the following new subclause after 4.9: To protect against excessive current, short-circuits and earth faults in circuits connected to an a.c. mains, protective devices shall be included either as integral parts of the equipment or as parts of the building installation, subject to the following, a), b) and c): a) except as detailed in b) and c), protective devices necessary to comply with the requirements of B.3.1 and B.4 shall be included as parts of the equipment; b) for components in series with the mains input to the equipment such as the supply cord, appliance coupler, r.f.i. filter and switch, short-circuit and earth fault protection may be provided by protective devices in the building installation; c) it is permitted for pluggable equipment type B or permanently connected equipment, to rely on dedicated overcurrent and short-circuit protection in the building installation, provided that the means of protection, e.g. fuses or circuit breakers, is fully specified in the installation instructions. If reliance is placed on protection in the building installation, the installation instructions shall so state, except that for pluggable equipment type A the building installation shall be regarded as providing protection in accordance with the rating of the wall socket outlet.</p>		N/A
5.4.2.3.2.4	<p>Add the following to the end of this subclause: The requirement for interconnection with external circuit is in addition given in EN 50491-3:2009.</p>		P
10.2.1	<p>Add the following to c) and d) in table 39: For additional requirements, see 10.5.1.</p>		N/A

IEC62368_1B - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
10.5.1	<p>Add the following after the first paragraph: <i>For RS 1 compliance is checked by measurement under the following conditions:</i> <i>In addition to the normal operating conditions, all controls adjustable from the outside by hand, by any object such as a tool or a coin, and those internal adjustments or presets which are not locked in a reliable manner, are adjusted so as to give maximum radiation whilst maintaining an intelligible picture for 1 h, at the end of which the measurement is made.</i> NOTE Z1 Soldered joints and paint lockings are examples of adequate locking. <i>The dose-rate is determined by means of a radiation monitor with an effective area of 10 cm², at any point 10 cm from the outer surface of the apparatus.</i> <i>Moreover, the measurement shall be made under fault conditions causing an increase of the high-voltage, provided an intelligible picture is maintained for 1 h, at the end of which the measurement is made.</i> <i>For RS1, the dose-rate shall not exceed 1 µSv/h taking account of the background level.</i> NOTE Z2 These values appear in Directive 96/29/Euratom of 13 May 1996.</p>		N/A
10.6.1	<p>Add the following paragraph to the end of the subclause: EN 71-1:2011, 4.20 and the related tests methods and measurement distances apply.</p>		N/A
10.Z1	<p>Add the following new subclause after 10.6.5. 10.Z1 Non-ionizing radiation from radio frequencies in the range 0 to 300 GHz The amount of non-ionizing radiation is regulated by European Council Recommendation 1999/519/EC of 12 July 1999 on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz). For intentional radiators, ICNIRP guidelines should be taken into account for Limiting Exposure to Time-Varying Electric, Magnetic, and Electromagnetic Fields (up to 300 GHz). For hand-held and body-mounted devices, attention is drawn to EN 50360 and EN 50566</p>		P
G.7.1	<p>Add the following note: NOTE Z1 The harmonized code designations corresponding to the IEC cord types are given in Annex ZD.</p>		N/A

IEC62368_1B - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
Bibliography	<p>Add the following standards:</p> <p>Add the following notes for the standards indicated:</p> <p>IEC 60130-9 NOTE Harmonized as EN 60130-9.</p> <p>IEC 60269-2 NOTE Harmonized as HD 60269-2.</p> <p>IEC 60309-1 NOTE Harmonized as EN 60309-1.</p> <p>IEC 60364 NOTE some parts harmonized in HD 384/HD 60364 series.</p> <p>IEC 60601-2-4 NOTE Harmonized as EN 60601-2-4.</p> <p>IEC 60664-5 NOTE Harmonized as EN 60664-5.</p> <p>IEC 61032:1997 NOTE Harmonized as EN 61032:1998 (not modified).</p> <p>IEC 61508-1 NOTE Harmonized as EN 61508-1.</p> <p>IEC 61558-2-1 NOTE Harmonized as EN 61558-2-1.</p> <p>IEC 61558-2-4 NOTE Harmonized as EN 61558-2-4.</p> <p>IEC 61558-2-6 NOTE Harmonized as EN 61558-2-6.</p> <p>IEC 61643-1 NOTE Harmonized as EN 61643-1.</p> <p>IEC 61643-21 NOTE Harmonized as EN 61643-21.</p> <p>IEC 61643-311 NOTE Harmonized as EN 61643-311.</p> <p>IEC 61643-321 NOTE Harmonized as EN 61643-321.</p> <p>IEC 61643-331 NOTE Harmonized as EN 61643-331.</p>		N/A

IEC62368_1B - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
ZB	ANNEX ZB, SPECIAL NATIONAL CONDITIONS (EN)		N/A
4.1.15	<p>Denmark, Finland, Norway and Sweden</p> <p>To the end of the subclause the following is added:</p> <p>Class I pluggable equipment type A intended for connection to other equipment or a network shall, if safety relies on connection to reliable earthing or if surge suppressors are connected between the network terminals and accessible parts, have a marking stating that the equipment shall be connected to an earthed mains socket-outlet.</p> <p>The marking text in the applicable countries shall be as follows:</p> <p>In Denmark: "Apparatets stikprop skal tilsluttes en stikkontakt med jord som giver forbindelse til stikproppens jord."</p> <p>In Finland: "Laite on liitettävä suojakoskettimilla varustettuun pistorasiaan"</p> <p>In Norway: "Apparatet må tilkoples jordet stikkontakt"</p> <p>In Sweden: "Apparaten skall anslutas till jordat uttag"</p>		N/A
4.7.3	<p>United Kingdom</p> <p>To the end of the subclause the following is added:</p> <p>The torque test is performed using a socket-outlet complying with BS 1363, and the plug part shall be assessed to the relevant clauses of BS 1363.</p> <p>Also see Annex G.4.2 of this annex</p>		N/A

IEC62368_1B - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
5.2.2.2	<p>Denmark</p> <p>After the 2nd paragraph add the following: A warning (marking safeguard) for high touch current is required if the touch current exceeds the limits of 3,5 mA a.c. or 10 mA d.c</p>		N/A
5.4.11.1 and Annex G	<p>Finland and Sweden</p> <p>To the end of the subclause the following is added: For separation of the telecommunication network from earth the following is applicable: If this insulation is solid, including insulation forming part of a component, it shall at least consist of either</p> <ul style="list-style-type: none"> • two layers of thin sheet material, each of which shall pass the electric strength test below, or • one layer having a distance through insulation of at least 0,4 mm, which shall pass the electric strength test below. <p>If this insulation forms part of a semiconductor component (e.g. an optocoupler), there is no distance through insulation requirement for the insulation consisting of an insulating compound completely filling the casing, so that clearances and creepage distances do not exist, if the component passes the electric strength test in accordance with the compliance clause below and in addition</p> <ul style="list-style-type: none"> • passes the tests and inspection criteria of 5.4.8 with an electric strength test of 1,5 kV multiplied by 1,6 (the electric strength test of 5.4.9 shall be performed using 1.5 kV), and • is subject to routine testing for electric strength during manufacturing, using a test voltage of 1,5kV. <p>It is permitted to bridge this insulation with a capacitor complying with EN 60384-14:2005, subclass Y2. A capacitor classified Y3 according to EN 60384-14:2005, may bridge this insulation under the following conditions:</p> <ul style="list-style-type: none"> • the insulation requirements are satisfied by having a capacitor classified Y3 as defined by EN 60384-14, which in addition to the Y3 testing, is tested with an impulse test of 2,5 kV defined in 5.4.11; • the additional testing shall be performed on all the test specimens as described in EN 60384-14; the impulse test of 2,5 kV is to be performed before the endurance test in EN 60384-14, in the sequence of tests as described in EN 60384-14. 		N/A
5.5.2.1	<p>Norway</p> <p>After the 3rd paragraph the following is added: Due to the IT power system used, capacitors are required to be rated for the applicable line-to-line voltage (230 V).</p>		N/A

IEC62368_1B - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
5.5.6	Finland, Norway and Sweden To the end of the subclause the following is added: Resistors used as basic safeguard or bridging basic insulation in class I pluggable equipment type A shall comply with G.10.1 and the test of G.10.2.		N/A
5.6.1	Denmark Add to the end of the subclause Due to many existing installations where the socket-outlets can be protected with fuses with higher rating than the rating of the socket-outlets the protection for pluggable equipment type A shall be an integral part of the equipment. <i>Justification:</i> In Denmark an existing 13 A socket outlet can be protected by a 20 A fuse.		N/A
5.6.4.2.1	Ireland and United Kingdom After the indent for pluggable equipment type A , the following is added: – the protective current rating is taken to be 13 A, this being the largest rating of fuse used in the mains plug.		N/A
5.6.5.1	To the second paragraph the following is added: The range of conductor sizes of flexible cords to be accepted by terminals for equipment with a rated current over 10 A and up to and including 13 A is: 1.25 mm ² to 1.5 mm ² in cross-sectional area.		N/A
5.7.5	Denmark To the end of the subclause the following is added: The installation instruction shall be affixed to the equipment if the protective conductor current exceeds the limits of 3.5 mA a.c. or 10 mA d.c.		N/A

IEC62368_1B - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
5.7.6.1	<p>Norway and Sweden To the end of the subclause the following is added: The screen of the television distribution system is normally not earthed at the entrance of the building and there is normally no equipotential bonding system within the building. Therefore the protective earthing of the building installation needs to be isolated from the screen of a cable distribution system. It is however accepted to provide the insulation external to the equipment by an adapter or an interconnection cable with galvanic isolator, which may be provided by a retailer, for example. The user manual shall then have the following or similar information in Norwegian and Swedish language respectively, depending on in what country the equipment is intended to be used in: "Apparatus connected to the protective earthing of the building installation through the mains connection or through other apparatus with a connection to protective earthing – and to a television distribution system using coaxial cable, may in some circumstances create a fire hazard. Connection to a television distribution system therefore has to be provided through a device providing electrical isolation below a certain frequency range (galvanic isolator, see EN 60728-11)" NOTE In Norway, due to regulation for CATV-installations, and in Sweden, a galvanic isolator shall provide electrical insulation below 5 MHz. The insulation shall withstand a dielectric strength of 1,5 kV r.m.s., 50 Hz or 60 Hz, for 1 min. Translation to Norwegian (the Swedish text will also be accepted in Norway): "Apparater som er koplet til beskyttelsesjord via nettplugg og/eller via annet jordtilkoplet utstyr – og er tilkoplet et koaksialbasert kabel-TV nett, kan forårsake brannfare. For å unngå dette skal det ved tilkopling av apparater til kabel-TV nett installeres en galvanisk isolator mellom apparatet og kabel-TV nettet." Translation to Swedish: "Apparater som är kopplad till skyddsjord via jordat vägguttag och/eller via annan utrustning och samtidigt är kopplad till kabel-TV nät kan i vissa fall medföra risk för brand. För att undvika detta skall vid anslutning av apparaten till kabel-TV nät galvanisk isolator finnas mellan apparaten och kabel-TV nätet."</p>		N/A
5.7.6.2	<p>Denmark To the end of the subclause the following is added: The warning (marking safeguard) for high touch current is required if the touch current or the protective current exceed the limits of 3.5 mA .</p>		N/A

IEC62368_1B - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
B.3.1 and B.4	<p>Ireland and United Kingdom</p> <p>The following is applicable: To protect against excessive currents and short-circuits in the primary circuit of direct plug-in equipment, tests according to Annexes B.3.1 and B.4 shall be conducted using an external miniature circuit breaker complying with EN 60898-1, Type B, rated 32A. If the equipment does not pass these tests, suitable protective devices shall be included as an integral part of the direct plug-in equipment, until the requirements of Annexes B.3.1 and B.4 are met</p>		N/A
G.4.2	<p>Denmark</p> <p>To the end of the subclause the following is added: Supply cords of single phase appliances having a rated current not exceeding 13 A shall be provided with a plug according to DS 60884-2-D1:2011. CLASS I EQUIPMENT provided with socket-outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules shall be provided with a plug in accordance with standard sheet DK 2-1a or DK 2-5a. If a single-phase equipment having a RATED CURRENT exceeding 13 A or if a poly-phase equipment is provided with a supply cord with a plug, this plug shall be in accordance with the standard sheets DK 6-1a in DS 60884-2-D1 or EN 60309-2. Mains socket outlets intended for providing power to Class II apparatus with a rated current of 2,5 A shall be in accordance DS 60884-2-D1:2011 standard sheet DKA 1-4a. Other current rating socket outlets shall be in compliance with Standard Sheet DKA 1-3a or DKA 1-1c. Mains socket-outlets with earth shall be in compliance with DS 60884-2-D1:2011 Standard Sheet DK 1-3a, DK 1-1c, DK1-1d, DK 1-5a or DK 1-7a <i>Justification:</i> Heavy Current Regulations, Section 6c</p>		N/A
G.4.2	<p>United Kingdom</p> <p>To the end of the subclause the following is added: The plug part of direct plug-in equipment shall be assessed to BS 1363: Part 1, 12.1, 12.2, 12.3, 12.9, 12.11, 12.12, 12.13, 12.16, and 12.17, except that the test of 12.17 is performed at not less than 125 °C. Where the metal earth pin is replaced by an Insulated Shutter Opening Device (ISOD), the requirements of clauses 22.2 and 23 also apply.</p>		N/A

IEC62368_1B - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
G.7.1	United Kingdom To the first paragraph the following is added: Equipment which is fitted with a flexible cable or cord and is designed to be connected to a mains socket conforming to BS 1363 by means of that flexible cable or cord shall be fitted with a 'standard plug' in accordance with the Plugs and Sockets etc (Safety) Regulations 1994, Statutory Instrument 1994 No. 1768, unless exempted by those regulations. NOTE "Standard plug" is defined in SI 1768:1994 and essentially means an approved plug conforming to BS 1363 or an approved conversion plug.		N/A
G.7.1	Ireland To the first paragraph the following is added: Apparatus which is fitted with a flexible cable or cord shall be provided with a plug in accordance with Statutory Instrument 525: 1997, "13 A Plugs and Conversion Adapters for Domestic Use Regulations: 1997. S.I. 525 provides for the recognition of a standard of another Member State which is equivalent to the relevant Irish Standard		N/A
G.7.2	Ireland and United Kingdom: To the first paragraph the following is added: A power supply cord with a conductor of 1,25 mm ² is allowed for equipment which is rated over 10 A and up to and including 13 A.		N/A

IEC62368_1B - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
ZC	ANNEX ZC, NATIONAL DEVIATIONS (EN)		N/A
10.5.2	Germany The following requirement applies: For the operation of any cathode ray tube intended for the display of visual images operating at an acceleration voltage exceeding 40 kV, authorization is required, or application of type approval (Bauartzulassung) and marking. <i>Justification:</i> German ministerial decree against ionizing radiation (Röntgenverordnung), in force since 2002-07-01, implementing the European Directive 96/29/EURATOM. NOTE Contact address: Physikalisch-Technische Bundesanstalt, Bundesallee 100, D-38116 Braunschweig, Tel.: Int +49-531-592-6320, Internet: http://www.ptb.de		N/A


ATTACHMENT TO TEST REPORT IEC 62368-1
Pictures of the EUT




NB800, total view



NB800, rear view




Mainboard V2.1, top view (without COM_I/O Module)



Mainboard V2.2, top view (with equipped COM_I/O Module)



Mainboard V2.2, bottom view



Detail view of COM_I/O Module